

# Proposed Working Draft

**X3T10/1143D**

**Revision 10  
July 23, 1997**

---

## Information Technology - SCSI Enhanced Parallel Interface - EPI

This is an internal working document of X3T10 of the Accredited Standards Committee X3. As such, this is not a completed report and has not been approved by Task Group X3T10. The contents may be modified by the X3T10 Task Group. This document is made available for review and comment only.

Permission is granted to members of X3, its technical committees, and their associated task groups to reproduce this document for the purposes of X3 standardization activities without further permission, provided this notice is included. All other rights are reserved. Any duplication for commercial or for-profit use is prohibited.

[Technical Editor's Note: This Rev contains a proposed outline and content based on technical information and editing time available to the editor as of July 23, 1997. Major additions and changes are made to the sections on grounding and hot plugging details. The section dealing with and latching and counting for REQ and ACK have been tentatively slated for some other document since this subject is not directly within the scope of EPI. A complete draft containing all sections is presently envisioned for the September meeting.]

NCITSASC X3T10 EPI Technical Editor:

Bill Ham  
Digital Equipment  
334 South Street  
Shrewsbury MA 01545  
(508) 841-2629 Ph  
(508) 841-5266 Fx  
HAM@subsys.enet.dec.com

---

Other Points of Contact:

X3T10 Chair  
John Lohmeyer  
Symbios Logic  
4420 ArrowsWest Drive  
Colorado Springs, CO 80907-3444  
Voice: 719 533-7560  
Fax: 719 533-7036  
Email: john.lohmeyer@symbios.com

X3T10 Vice-Chair  
Lawrence J. Lamers  
Adaptec  
691 South Milpitas Blvd  
San Jose, CA 95035  
408 957-7817  
408 957-7193  
ljlammers@aol.com

X3 Secretariat

Lynn Barra  
Administrator Standards Processing  
X3 Secretariat  
1250 Eye Street, NW Suite 200  
Washington, DC 20005

Telephone: 202-626-5738  
Facsimile: 202-638-4922

SCSI Reflector

Internet address for subscription to the SCSI reflector:  
Internet address for distribution via SCSI reflector:

majordomo@symbios.com  
scsi@symbios.com

SCSI Bulletin Board

719-533-7950

Document Distribution

Global Engineering  
15 Inverness Way East  
Englewood, CO 80112-5704

Telephone: 303-792-2181 or  
800-854-7179  
Facsimile: 303-792-2192

**ABSTRACT**

This document describes SCSI configurations that may be achieved within the context of the specifications in the SCSI-2, SCSI-3 SPI, SPI-2, and SCSI-3 FAST 20 standards. These configurations have one or more configuration parameters expanded beyond that formally specified in the standard documents and may require special components, special restrictions, or an interpretation of the underlying technical reasons for parameters specified in the standards. This technical report describes the considerations that can lead to effective implementations of special components but does not describe the detailed design of any component. The information in this document does supersede any requirements in the referenced standards for formal compliance with standards.

**PATENT STATEMENT**

**CAUTION:** The developers of this technical report have requested that holders of patents that may be required for the implementation of the technical report, disclose such patents to the publisher. However, neither the developers nor the publisher have undertaken a patent search in order to identify which, if any, patents may apply to this technical report.

As of the date of publication of this technical report and following calls for the identification of patents that may be required for the implementation of the technical report, no other such claims have been made. No further patent search is conducted by the developer or the publisher in respect to any standard or technical report processes. No representation is made or implied that licenses are not required to avoid infringement in the use of this technical report.

## TABLE OF CONTENTS

1. Scope .....	4
2. References .....	4
3. Definitions, symbols, and abbreviations .....	4
3.1. Bus related .....	4
3.2. SCSI domain related .....	6
4. General .....	7
5. Bus segment concept .....	7
5.1. Segment length parameters .....	8
5.1.1. Protocol timing limits .....	9
5.1.1.1. Device loading parameters .....	9
5.1.1.2. Caution when using differential interfaces .....	9
5.1.2. Propagation - time - limited domain length .....	9
5.1.3. Signal quality limits .....	10
5.1.4. Printed Wire / circuit board parameters .....	11
5.2. Other segment properties .....	11
6. Bus segment length guidelines .....	11
6.1. Bus segment loading .....	11
6.2. Maximum speed of operation .....	12
6.3. Other segment guidelines .....	13
6.4. Comments on the segment length rules .....	13
6.5. Segment length tables .....	15
7. Mixed width operation .....	18
7.1. Architectural Options .....	18
7.1.1. 16 bit main path .....	18
7.1.1.1. Async, slow, fast-10, and fast 20 cases .....	18
7.1.1.2. Fast-40 case .....	19
7.1.2. 8 bit main path .....	19
7.1.3. Single 16 bit path and single 8 bit path .....	21
7.1.4. Multiple 8 or 16 bit paths .....	21
8. Bus expanders .....	22
8.1. Simple expanders .....	22
8.1.1. Homogeneous type .....	23
8.1.2. Heterogeneous types .....	23
8.1.3. Domain parameters using simple expanders only .....	23
8.1.4. General rules for SCSI domains using only simple expanders .....	24
8.1.4.1. Rule summary .....	24
8.1.4.2. Rule 1 .....	24
8.1.4.3. Rule 2 .....	24
8.1.4.4. Rule 3 .....	26
8.1.4.4.1. Effects of Wired-Or glitches .....	26
8.1.4.4.2. Effects of slow response to BUS FREE .....	26
8.1.4.4.3. Expander propagation delay effects .....	26
8.1.4.4.4. Sample calculations .....	27
8.1.4.5. Rule 4 .....	28
8.1.4.6. Rule 5 .....	28
8.1.4.7. Rule 6 (REQ/ACK offset) .....	28
8.2. Bridging expanders .....	30
8.2.1. General rules for SCSI domains using only bridging expanders .....	30
8.2.1.1. Expanded device counts in a single domain .....	30
8.2.1.2. Logical unit bridges .....	30
8.2.1.2.1. Initiator / target placement .....	30
8.2.1.2.2. Multi initiator considerations .....	30
8.2.1.2.3. Reserved ID's on target side .....	30
8.2.1.2.4. Relationship to Raid models .....	30
8.2.1.2.5. Impact on SCAM .....	30
8.2.1.2.6. Target considerations .....	30
8.2.1.3. Host considerations .....	30
8.2.1.4. Protocol implications .....	30
9. Dynamic reconfigurations .....	30
9.1. Addition and removal of devices .....	30

9.1.1. Framework of entire process.....	30
9.1.2. Electrical considerations .....	31
9.1.3. Logic input states during transitions .....	34
9.1.4. Protocol implications.....	35
9.2. Addition and removal of bus segments.....	35
10. Topologies and configuration rules for dynamically reconfigurable systems.....	36
10.1. Initiator placement .....	36
10.2. Redundant paths.....	36
10.3. Initialization .....	36
10.4. Power considerations.....	36
11. Terminator power distribution.....	36
11.1. Wire effects .....	37
11.1.1. Single ended.....	37
11.1.2. Low voltage differential (LVD) .....	39
11.1.3. Multimode SE/LVD.....	39
11.1.4. High voltage differential .....	39
11.2. Mixed power configurations .....	39
11.2.1. High voltage / Low voltage .....	39
11.2.2. Power on / Power off segments.....	39
11.3. Terminator considerations .....	39
11.4. TERMPWR source placement .....	39
12. Grounding.....	39
12.1. Single ended systems .....	<b>Error! Bookmark not defined.</b>
12.2. Differential systems .....	<b>Error! Bookmark not defined.</b>
13. References and tables.....	41
13.1. SFF-8017 reference.....	41
13.1.1. Wiring tables.....	42

**1. Scope**

This document is an ANSI technical report that provides guidance to experienced implementers and users of parallel SCSI beyond that contained in the formal standards.

**2. References**

- SCSI-2
- SCSI-3 SPI
- SCSI-3 Fast 20
- SPI-2

**3. Definitions, symbols, and abbreviations**

**3.1. Bus related**

Bus Segment:

A SCSI bus segment consists of all the conductors and connectors required to attain signal line continuity between every driver, receiver, and two terminators for each signal. It is not necessary that a SCSI bus segment contain any initiators or targets but it must have at least two devices attached. [drivers and receivers may be part of expanders as well as part of initiators and targets].

The allowed length of a bus segment depends on the electrical loading, type of transmission media, and data transfer rate. In many cases heavier loading, smaller wires, and higher speeds demand shorter lengths. Loading is produced by increasing the number of devices in a given length of bus or

by using longer stubs or higher capacitance devices. The details of the segment length limits are given in section 6, Table 1, Table 2, and Table 3.

Device:

Devices include targets, initiators, bus expanders (see definition in section 3.2).

Terminator:

Interconnect components that form the ends of the transmission lines in bus segments. A SCSI domain (section 3.2) must have at least one segment and therefore at least two terminators (except for special cases where the electrical transmission lines are very short).

Bus segment types:

There are presently three types of SCSI bus segment:

- Single ended (SE)
- High voltage differential (HVD)
- Low voltage differential (LVD).

The bus segment type is determined by the properties of the terminators used. Devices that do not have the same transceiver type as the terminators cannot operate in the segment defined by the terminators.

Bus-path:

The electrical connection directly between the two terminators in a bus segment is a bus path.

Stub:

Any electrical path in a bus segment that is not part of the bus-path.

Stub connection:

The point where a stub meets the bus-path.

Transmission medium (media)

An electrical conductor having bus termination on each end and possibly stubs. Common examples of media are cables, printed wiring boards, backplanes, flex circuits, and connectors that create the electrical connections between SCSI devices and/or bus expanders (see below) and terminators.

SCSI bus (segment) connector:

Any connector used to create a SCSI bus segment. SCSI bus connectors are defined both by their function AND by their physical placement. There are only two allowed functions: bus-path and stub. There are numerous physical placement descriptions. Examples of SCSI bus connectors are "device stub connector" and "terminator bus-path connector"

Bus-path connector (functional description)

Any connector used to provide part of the bus-path

Stub connector (functional description)

Any connector used to provide part of a stub

Device connector (physical placement description)

Any connector physically part of SCSI device

Cable connector (physical placement description)

Any connector that is physically part of a cable assembly, attached to backplanes, or other non-device conductors

Terminator connector (physical placement description)

Any connectors physically part of a terminator. It is not uncommon for terminators to have both stub and bus-path connectors (See Figure 1).

Enclosure connector (physical placement description)

Any connector that is physically part of an enclosure

Other physical placement descriptions may be used.

Special note for location of stub connection point:

The mating interface of stub connectors is considered to be the stub connection if the path between the true stub connection and the mating interface is contained wholly within the connector housing\*. Such connectors are termed housing-only connectors.

\*[This condition is common for connectors that are directly attached to flat ribbon cable. The true stub connection is the point where the wire of the ribbon cable meets the IDC part of the connector pin. The stub contained within the connector is very short and the true point of stub connection is not easily physically accessible so there is very little margin lost by considering the mating interface as the true stub connection.]

Figure 1 shows examples of connectors, bus paths, stubs, and stub connections in a single bus segment.




Figure 1 - Single segment physical architecture and terminology examples

3.2. SCSI domain related

SCSI domain:

A SCSI domain is a logical bus with at least one bus segment, at least one initiator, and at least one targets. Domains with multiple bus segments are enabled through the use of bus expanders. Domains are limited by the device addressability. Domains are limited to a maximum of 16 initiators and/or targets without the use of bridging expanders.

Simple expander

Devices that couple bus segments together without any impact on the SCSI protocol or software/firmware are called simple bus expanders. See 8.

Bridging expander

Devices that couple a bus segment to another SCSI segment or another kind of port by using addressable SCSI ports.

#### 4. General

This document describes configurations and extensions that are possible within the context of the existing SCSI standards but that may not be obvious or formally allowed by the standards. It is the intent of this document to provide technical information and guidance to enable these expanded capabilities in an effective way.

The common theme on all of these enhancements is expansion of applications that can be addressed without changing the features of existing SCSI device implementations that comply with the existing standards. Of special interest are interconnecting devices capable of different widths, extending the physical length of the SCSI domain, increasing the dynamic reconfigurability of domains, and extending the number of addressable devices in a single domain.

#### 5. Bus segment concept

Existing SCSI standards define parameters for SCSI busses based on the assumption that there is a single electrically conducting path between bus terminators for each signal and that a SCSI domain contains all the devices between these two terminators. This electrical path is assumed to pass signals in both directions without delay other than that caused by the propagation delay of the transmission line associated with the path. It is assumed that there are no intervening active components in the path between the bus terminators.

A more general concept recognizes that it is possible to build SCSI domains that use more complex physical implementations where there may be active electrical components between SCSI devices. A building block for these more complex implementations is the bus segment which is defined as two bus terminators and the associated single electrically conducting path between these terminators (for each signal) that satisfies the assumptions in the first paragraph of this section. Multiple bus segments may be functionally connected together by special coupling circuits described in section 8.

Each bus segment has TERMPower sources and TERMPower distribution parameters.

Bus segments must use the same transmission type (differential, LVD SCSI, or single ended) within the segment. A domain may contain segments that use different transmission types.

Bus segments largely follow the same rules individually that are described in the existing standards (with important exceptions). Using multiple bus segments with coupling circuits in the same domain allows much more of the full properties supported by the SCSI bus protocol to be realized than when using single segment domains.

Some of the salient properties impacted are device count limits, physical length limits, ground voltage shifts, dynamic removal and replacement of portions of domains, and mixing of device types (single ended, high voltage differential, and low voltage differential).

##### 5.1. Segment length parameters

The existing SCSI-2 and SCSI-3 SPI standards mention physical lengths as recommended or required maximums for certain conditions. The SCSI-3 Fast 20 standard incorporates information that allows implementers significant leeway in the maximum physical lengths through the use of informative material provided in annexes. The reasons behind the length numbers contained in the existing standards are not always stated in the standards and some of the technology that existed some years ago has improved significantly since these standards were stabilized. Both of these points invite re-examination of length related parameters based on the latest knowledge and technology.

The concept of a bus segment is introduced for the first time in this document. Using multiple bus segments in the same SCSI domain directly challenges the notion of using physical length alone as a domain configuration limit. In order to understand and give guidance concerning appropriate physical length of bus segments and domains one must look at the properties that affect this length.

Bus segments and SCSI domains have physical length limits that are determined by (1) the time required for signal propagation or (2) by loss of signal quality due to resistance, dispersion, delay skew, transmission line reflections, jitter or other factors. As long as the physical plant delivers the signals to SCSI device connectors and bus terminators with the proper timing and signal quality there is no technical reason to further restrict the

physical length. These criteria must be applied to the lines that first fall outside of acceptable bounds as the length is increased. In some cases the TERMPWR lines limit the length. See section 11.

For the domain length limits one must consider the propagation time consumed by the elements that connect the bus segments as well as that consumed in the individual segments. The length limits for individual segments may be independently considered as long as the domain length (protocol timing) limits are not exceeded. A single domain may contain many segments since some of the most attractive versions of SCSI have very short segment length limits (caused by signal quality) that consume only a small part of the domain timing budget.

Section 8 considers the propagation delay issues for the elements that connect bus segments. The remainder of this section considers the factors that affect the physical length of single segment domains and segments within multisegment domains.

### 5.1.1. Protocol timing limits

The SCSI arbitration and service boundary protocols define a time of 400 ns for the bus to "settle" after certain conditions described in the SCSI-3 SIP document are possible. The intent of this "bus settle delay" is to allow a full round trip time for electrical disturbances to decay before proceeding to the next steps in the protocol. This means that the overall time required for a signal to travel from one end of the bus to the other and to "reflect back to the beginning" is a maximum of 400 ns. A one way transit time of 200 ns must be used for each segment. It may be possible to extend the one way time to 400ns for a multi-segment domain. See 8.1.3. Even in this case each segment must individually meet the 200 ns one way requirement.

If one has a uniform bus media and a known signal propagation velocity,  $V_p$ , this establishes the maximum physical length as  $L_{max} = 200ns/V_p$ . With the presently allowed slowest  $V_p$  of approximately 5ns/m this gives a maximum length of 40 meters. One cannot use this number as a general limit because the transmission media is not uniform and the signals are delayed by the non-uniformities. The next section considers the most important additional effects caused by device loading.

#### 5.1.1.1. Device loading parameters

When real devices are present on a segment their stubs and capacitive loads add to the bus delay for the signals. The amount of this delay depends on the details of the loading. In the normal worst case with a 0.1 meter stub and a 25 pF capacitive load this delay has been reported to be approximately 0.5 ns per device.

In general the allowed transit time must be reduced by the delay caused by the loads. The device delay is denoted  $T_{di}$  for the "i"th device and the total delay is the sum of the delays from all devices on the domain (including any segment connecting elements) and is denoted  $T_{dd}$ .

This gives a general formula for the maximum domain length as:

$$L_{max} = (200ns - T_{dd}) / V_p$$

With 14 devices having a total of 0.5 ns per device there is a 7 ns reduction. One should also allow some delay for connectors and other disturbances. A reasonable number for this may be 2 ns for a domain having several connectors.  $T_{dd}$  therefore becomes approximately 9 ns for a fully loaded wide SCSI segment

#### 5.1.1.2. Caution when using differential interfaces

It is important to note that the times relating to the signal propagation are defined as measured from the device connectors. This is especially important when using differential interfaces with separate transceivers since the propagation time through the transceivers can be several tens of nanoseconds. The SCSI standard does not allow any special budget for these extra transceiver delays so designers of differential interfaces must ensure that the timings of protocol chips and other device design parameters accommodate separate transceivers.

### 5.1.2. Propagation - time - limited domain length

Using the numbers in section 5.1.1.1 and assuming a  $V_p$  of 5 ns/m we find a maximum single segment length (with reflections) to be  $191/5 = 38.2$  meters. The number in the present standards use a much more conservative  $V_p$  of 6.6 ns/m (28.93m) and adds extra margin to report a maximum length of 25 meters. Using the real numbers without the extra margin we gain an extra 13.2 meters in total segment length. For media specially built for high propagation velocity one can achieve at least 3.76ns/m for a loaded length of 50.8m or double that in the present standards without changing any protocol timings (if the signal quality remains adequate).

Lengths above 6 meters are suggested as mainly applicable to differential transmissions in the standards. We will examine this assumption in more detail in section 5.1.3.

It is not necessary to abandon the length based scheme to achieve the benefits of multisegment domains but it is necessary to adopt some relationship between length and time to allow for the coupling circuits between domains. This relationship can be provided by the equation in section 5.1.1.1. One may think of the length based scheme as a significantly conservative specification method.

### 5.1.3. Signal quality limits

This section explores the effects of segment lengths on signal quality.

There are two factors related to length that affect signal quality: attenuation and the duration of reflections. When a reflection is needed to achieve a useable signal size it is vital that this reflection reach the receiver before the next pulse edge. The pulse will never reach a detectable level if this does not happen. A second consequence of the reflection being too long is disturbance of subsequent pulses and very complex interactions between pulses.

Attenuation becomes a limiting factor for long, lightly loaded and point to point segments. It is the a.c. attenuation that contributes most when attenuation is the limit. The lengths necessary to reach attenuation limited conditions far exceed that for reflection limited lengths. This statement may not apply if one is using very small gauge wire (less than 32 gauge). In the normal situation where 32 gauge or larger wire is being used one can readily establish some conditions that relate segment length to keeping the first reflection within the same pulse. This condition is simply that the round trip propagation time be less than the minimum assertion or negation period for the signals.

The minimum assertion/negation period varies with the synchronous data transfer rate. Slow SCSI has a period of 90 ns, fast is 30 ns, fast 20 is 15 ns, fast 40 is 8 ns. Assuming a propagation velocity of 5 ns/meter one can go 18 meters in 90 ns, 6 meters in 30 ns, 3 meters in 15 ns, and 1.6 meters in 8 ns. Since these are round trip times one would get 9, 3, 1.5, and 0.8 meters respectively as the maximum length possible before the reflection could exceed the assertion/negation period. These lengths match perfectly the recommendations in the standards for fast and fast 20 and show that slow SCSI has relatively more margin in this respect.

It is appropriate to consider that a significant decrease in noise margin exists when these reflection length limits are exceeded. For example if one exceeds the 3 meter limit for fast SCSI he should expect that reflections would need to be under very good control or some other features would need to be better than minimally required.

The condition where there is no need for a reflection to achieve a good detectable signal is called incident wave switching. This simply means that the first pulse edge actually gets detected. The published length limits of 6, 3, and 1.5 meters for slow, fast and fast 20 are rendered unnecessary if one can guarantee that incident wave switching will occur. If one is in an incident wave switching mode there is a possibility of complex interactions between pulses since the reflections (although not needed for initial switching) may appear in pulses other than those where they originated. With incident wave switching even the single ended fast 20 segments may reach well beyond the 1.5 meter limit toward the 25+ meter controlled by the bus settle delay.

When not assuming an incident wave switching mode there are parameters within the segment that can provide additional margin. The most important of these is the loaded characteristic impedance of the segment. The better this matches the unloaded case the higher the noise margin. Another parameter is the propagation velocity of the loaded media for the segment. The faster this velocity the quicker the reflections arrive and the more high level pulse is available for detection. Watch out for an unfortunate relationship between these two parameters. In order to increase the propagation velocity it is usually necessary to decrease the capacitance per unit length of the media. This decrease makes the loaded characteristic impedance more easily affected by loads. However, since we were assuming non incident wave switching anyway it is quite likely that the higher propagation velocity will result in a net increase in noise margin. Cables made with FEP, TPE and "PTFE" generally offer somewhat higher noise margin because of their increased propagation velocity.

The factor that most likely forces one out of the incident wave switching mode is clustered loads on the segment media. All else being equal the capacitance per unit length of the media is the single most important property that affects its ability to withstand clustered loads. Media with higher capacitance are disturbed less by loads. Fortunately, where we need higher capacitance the most (in backplane applications) it actually exists in the media.

#### 5.1.4. Printed Wire / circuit board parameters

Printed circuit boards with the right characteristic impedance usually have much higher capacitance per unit lengths than cables and therefore are better suited to handle clustered loads. The cable to PCB capacitance ratio is frequently around 0.5 or lower. While this helps the desire to have devices close together it also produces a greater sensitivity to stub length. Stubs in a backplane should be reduced by at least twice over a cable implementation.

Printed circuit boards may have much higher attenuation per unit length than a cable. This is usually not a concern since PCB's have short us lengths.

#### 5.2. Other segment properties

Segments offer not only confinement for reflections they also offer the possibility of separating grounds within a domain by using multiple segments for the domain. Within any segment strict observance of the ground shift requirement is necessary.

### 6. Bus segment length guidelines

As discussed in 5 there are three main features that determine the maximum bus segment length: bus settle delay, electrical loading by devices, and maximum speed of operation. This relates to propagation delay, needing reflections and a.c. attenuation respectively. In addition, there a number of other requirements that apply independent of these features.

In this section guidelines based on some bus loading conditions are presented that indicate the maximum length that may be achievable. These loading conditions are specified in greater detail than available in the existing standards and include important conditions that are not addressed in the existing standards.

A three level class system used for these guidelines where risk is varied by class. The lowest risk class, class 1, largely reflects parameters and loading conditions listed in the standards documents. Class 2 guidelines consider loading conditions not directly considered or not adequately considered in existing standards. The lengths listed under class 2 reflect experience with testing results to support the parameters. Class 3 guidelines consider conditions that go beyond that considered in classes 1 and 2. The lengths listed under class 3 should be possible under careful implementation conditions but have not had any significant verification or testing. Using class 3 guidelines is the highest risk and requires more attention to details and experience with SCSI implementations. There are some conditions where no guidance is presented due to lack of available data.

#### 6.1. Bus segment loading

Five categories of loading are defined:

##### 1) Point to point using uniform bus media

This case is the least demanding on the transmission interconnect. Only two electrical loads may be present near the terminators in the segment,. This case is commonly found between host adapters and disk controllers, for single remote tapes and other devices, and for length extension segments between expanders. See 8.

Uniform bus media means same style of cabling used throughout (e. g. round shielded only). In-line connectors are allowed.

##### 2) Devices spaced at least 1 meter apart using uniform bus media

This case is a normally very electrically friendly case commonly found when daisy chaining multiple external enclosures with external shielded Y cables. Enclosures that use internal ribbon cabling may not work well in this application.

3) Devices spaced at least 8" apart (cables)

This case is found within enclosures such as PC's, workstations, and for some closely spaced external enclosures. It is more electrically demanding than case 2 because the devices are placed closer together and because cables are sometimes not as good as backplanes at accommodating device loads.

For certain heavily loaded cases the lengths must be reduced below that used for the more lightly loaded cases.

4) Devices spaced at least 4" apart (backplanes)

This case is a common backplane condition when using 3.5" form factor devices. It is able to accommodate closer spacing because the backplane interconnect is better able to absorb the device loads. When cables are attached directly to the backplane significant extra signal degradation is usually experienced so the simple length rules must be modified.

Very significant benefit is expected by using expander circuits directly off the enclosures that have backplane interconnect.

5) Devices spaced at least 4" apart with 8" stubs (backplanes)

This case is found in some backplane configurations that use large form factor devices. It is perhaps the most demanding condition for the interconnect.

There is some correlation between large form factor devices and higher device capacitance which makes it unclear whether the stub length or the higher capacitance is the main cause of the signal degradations for this class of configuration. Part of the increased capacitance comes from the stub itself but in some cases it is the device that is mainly responsible.

It is expected that the use of expanders on the backplane enclosures will allow the large form factor configurations to operate at all speeds.

Special note for bus expanders (See 8): All SCSI bus expanders are treated as a device when counting electrical loads. Even though expanders do not occupy SCSI ID's they still produce electrical loading. Expander loads can be important if the segment length depends on the number of devices.

## 6.2. Maximum speed of operation

There are five bus transfer rates presently identified:

Asynchronous, slow, fast (fast 10), fast 20, and fast 40

Each of these transfer rates is applied to the synchronous data phase only except the asynchronous which applies to all phases except the synchronous data phase. It is frequently possible to operate a bus segment in the asynchronous speed mode when it will not work in a high speed synchronous mode. In other cases a very slow synchronous mode may be the most friendly. For configurations that will not operate under one speed mode the speed may be changed.

Operation in a slower speed mode will frequently keep the system alive and will allow in-band communication for diagnostic purposes as long as the basic electrical connections are in place.

The successful operation of bus segments and SCSI domains at the maximum rate requires that the bus segments operate within prescribed length and loading parameters.

### 6.3. Other segment guidelines

All single ended segments are assumed to be terminated with active, linear terminators properly placed in the bus segment. This does not mean that other termination schemes cannot work well in many applications but the specific data in this document only addresses the referenced kind of terminator.

All differential segments are assumed to be terminated with linear, totem pole terminators as specified in the SCSI standards, properly placed in the bus segment.

Single ended segments have ground distribution systems that control ground offset to less than 50 mV. (Normal good installations have ground offsets much less than 50 mV) This ground offset requirement applies at the logic ground of the SCSI devices which may not always be at the same ground as the chassis. SCSI devices should normally have the logic ground connected directly to the chassis ground to ensure that this requirement is met.

Differential segments have the ground offset controlled to less than 350 mV for LVD and 500 mV for HVD. The same comments concerning logic/chassis ground apply as for single ended above.

The maximum stub length is assumed to be 4" for single ended and LVD and 8" for HVD unless otherwise noted. Stubs are any electrical path within the segment that is not part of the bus path. (The electrical path between the terminators is the bus path). Stub length is measured from the point of attachment to the bus path to the farthest point along the stub path. Frequently the end of the stub will be at a chip bonding pad within a chip package.

The maximum device pin capacitance to ground for single ended devices is 25 pF measured at 0.5V d. c.

Differential capacitance is measured as C1/C2/C3 following the LVD spec where C1 is the capacitance from + signal to ground, C2 is the capacitance from - signal to ground and C3 is between + signal and - signal. For HVD SCSI the maximum capacitance is 30/30/15 pF and for LVD SCSI the maximum capacitance is 20/20/10 pF.

For devices located very near (within 4 inches) one of the SCSI bus terminators the allowed device capacitance may be increased to the point where the combination of the terminator capacitance and the device capacitance does not exceed 50 pF for single ended or 40/40/20 for differential. Note that this MUST be at a position where the terminator is actually being used for bus termination. Devices that use switchable terminators only qualify under this condition if the terminator is switched on AND the device is the end of the bus segment providing one of the two bus segment terminations. Therefore at most 2 higher capacitance devices per segment are allowed.

Cable media complies with the appropriate SCSI standard.

### 6.4. Comments on the segment length rules

There is presently little data available to determine for sure exactly what the effects of using single ended to single ended expanders will be.

The experience with the present single ended to HVD expanders provides significant confidence that the extrapolations in this rev of the document are likely to be accurate.

The extended single ended lengths (beyond 6 meters) are based on actual testing of single ended systems and experience with differential systems that actually operate at the longer lengths. The timing properties of the differential implementations are more demanding than the single ended versions and both the signal integrity and actual full protocol operation have been verified at these extended single ended lengths. The risk here is lack of broad experience with real single ended devices at these extended lengths.

Some async configurations have not been tested and therefore have class 3 designation. If the silicon in the SCSI protocol chips has been properly designed these async configurations should work even if the signal integrity is very poor on the pulse edges.

For LVD SCSI the lengths indicated may appear to eliminate the need for expanders. This is not a valid interpretation since isolation may be required to achieve hot plugging and will be required for configuration

flexibility. Data from multimode backplanes indicates that expanders will be needed between the backplane and external cable for cables longer than approximately 3 meters. Further, most of the presently available LVD data is class 2 based on signal quality and timing analyses only. Only the point to point data has presently been tested with full protocol devices.

6.5. Segment length tables

Table 1 - Length limits for single ended SCSI bus segments

TRANSFER RATE	RULE CLASS	POINT TO POINT WITH UNIFORM BUS MEDIA	LOADS SPACED AT LEAST 1 METER APART WITH UNIFORM BUS MEDIA	LOADS SPACED AT LEAST 8" APART (CABLES)	LOADS SPACED AT LEAST 4" APART (BACKPLANES)	LOADS SPACED AT LEAST 4" APART WITH 8" STUBS (BACKPLANES)
ASYNC	1	6	6	6	6	
	2	20***	20	20	20	6 ??
	3	35	25	25	25	20
SLOW	1	6	6	6	6	1; 5 LOADS*
	2	20***	6			
	3	35	15			
FAST 10	1	3	3	3; 8 LOADS 2.2; 16 LOADS	3; 8 LOADS 2.2; 16 LOADS	1; 5 LOADS*
	2	20***	6			
	3	35	15			
FAST 20	1	3	3	1.5; 8 LOADS 3; 4 LOADS	1; 8 LOADS*	1; 5 LOADS*
	2	20***	4			
	3	35				
FAST 40**						
* REQUIRES EXPANDER WITHIN 8" OF BACKPLANE						
** FAST 40 SINGLE ENDED IS NOT PRESENTLY DEFINED						
*** TWO LOADS WITHIN 0.5 METER OF THE TERMINATOR ARE ALLOWED ON EACH END						

Rule classes:

1. derived from field and lab testing
2. derived from the known behavior of the SCSI bus and has been tested but have not been extensively tested or used
3. projected to be possible with custom control of all components in the segment and special analysis performed by SCSI experts

Loading: 1 load is a maximum capacitance / maximum stub length device (including expanders) (25 pF / 0.1 meter)

All length data in meters

**Table 2 - Length limits for high voltage differential SCSI bus segments**

TRANSFER RATE	RULE CLASS	POINT TO POINT	LOADS SPACED AT LEAST 1 METER APART	LOADS SPACED AT LEAST 8" APART (CABLES)	LOADS SPACED AT LEAST 4" APART (BACKPLANES)	LOADS SPACED AT LEAST 4" APART WITH 8" STUBS (BACKPLANES)
ASYNC	1	25	25	25	?	?
	2	35	35	35	?	?
	3				25	25
SLOW	1	25	25	25	?	?
	2	35	35	35	?	?
	3				25	25
FAST 10	1	25	25	25	?	?
	2	35	35	35	?	?
	3				25	25
FAST 20	1	25	25	25	?	?
	2	35	35	35	?	?
	3				25	25
FAST 40	1	?	?	?	?	?
	2	25	12	12	?	?
	3	35	25	20	20	?

Rule classes:

1. derived from field and lab testing
2. derived from the known behavior of the SCSI bus and has been tested but have not been extensively tested or used
3. projected to be possible with custom control of all components in the segment and special analysis performed by SCSI experts

Loading: 1 load is a maximum capacitance / maximum stub length device (including expanders) (25/25/12.5 pF / 0.2 meter)

All length data in meters.

**Table 3 - Length limits for low voltage differential SCSI bus segments**

TRANSFER RATE	RULE CLASS	POINT TO POINT	LOADS SPACED AT LEAST 1 METER APART	LOADS SPACED AT LEAST 8" APART (CABLES)	LOADS SPACED AT LEAST 4" APART (BACKPLANES)	LOADS SPACED AT LEAST 4" APART WITH 8" STUBS
ASYNC	1					****
	2	25	25	12		
	3	35	35	20	15	
SLOW	1					****
	2	25	20	15	12	
	3	35	35	20	15	
FAST 10	1					****
	2	25	20	15	12	
	3	35	35	20	15	
FAST 20	1					****
	2	25	15	15		
	3	35	35		15	
FAST 40						****
		25	12	12		
		35	35		12	
**** NOT PRESENTLY KNOWN -- THIS CONDITION IS MORE AFFECTED BY CAPACITIVE LOADING THAN BY STUB LENGTH -- THIS CONFIGURATION ONLY LIKELY TO WORK WITH BACKPLANES WITH 4 OR FEWER DEVICES PER BACKPLANE -- PROBABLE NUMBERS SAME AS FOR 4" STUBS						

Rule classes:

1. derived from field and lab testing
2. derived from the known behavior of the SCSI bus and has been tested but have not been extensively tested or used
3. projected to be possible with custom control of all components in the segment and special analysis performed by SCSI experts

Loading: 1 load is a maximum capacitance / maximum stub length device (including expanders) (20/20/10 pF / 0.1 meter)

All length data in meters.

## **7. Mixed width operation**

SCSI is specified to operate with any of three data path widths: 8 bit, 16 bit, and 32 bit. This document does not consider the 32 bit operation. Conditions exist where it is desirable to implement both 8 and 16 bit SCSI devices within the same bus segment. When this happens the bus segment is said to be using mixed width operation.

Since the timing requirements become more strict at higher data rates the risk of using mixed width operation increases at higher data rates. The details of these risks are explored in this section.

### **7.1. Architectural Options**

This section describes four different ways to configure mixed width bus segments. Each requires separate consideration and each must adhere to the wiring tables shown in 13.1.1.

#### **7.1.1. 16 bit main path**

##### **7.1.1.1. Async, slow, fast-10, and fast 20 cases**

The simplest form of mixed width segment has a 16 bit main path to which either 8 bit devices, 16 bit devices, or both are attached. Only the 16 bit main path has bus termination. No 8 bit devices may provide any bus termination.

Figure 2 shows the architecture of this implementation. Every 8 bit connection only contacts the SCSI lines that are used for 8 bit devices. The upper 9 bits (data and parity) are not contacted by the 8 bit device. This condition produces more electrical load on the lower 9 bits (data and parity) than on the upper 9 bits.




Figure 2 - Mixed width connections using 16 bit main path

This non-uniform loading produces timing skew in direct proportion to the number of 8 bit devices used and the electrical load they present. The worst case is when two 16 bit devices are near the opposite ends of the bus and there are 8 8-bit devices in between. One could have 14 8 bit devices in between but this case could not work since there are only 8 address bits available on 8 bit devices and only 8 devices can be addressed. In this case there is 8 times the individual device loading skew on the data lines. Measurements have shown that a typical delay induced by a single device is 0.5 ns. The one way timing skew in this worst case situation is therefore approximately 4 ns. This is larger than the timing skew produced by the cable media itself and could be responsible for data errors in the upper 9 bits if not treated.

One way to lessen the impact of the non-uniform loading is to add electrical load to the upper 9 bits by the connection scheme used between the 8 bit devices and the 16 bit path.

If the 16 bit path uses the common 0.025" centerline flat ribbon cable there will be a connector conversion necessary to attach the 8 bit device. The connection to the flat ribbon cable will require a high density 68 pin connector while the 8 bit device will require a 50 pin low density connector. It is convenient to add discrete capacitors within the connector converter device between each of the upper 9 bits and a ground line. The value of the capacitors should be approximately the same as the pin capacitance of the 8 bit device. Of course not all 8 bit devices have the same pin capacitance but a reasonable approximation is from 10 to 20 pF.

This compensation scheme can significantly reduce the skew to levels that are generally negligible.

If one is using round cable (either shielded or unshielded) for the 16 bit path it is possible to use the 50 pin low density connector directly to the 16 bit path. In this case one should be careful not to break the conductors while attaching this connector in order to maintain equal path lengths for the lines. There is no readily convenient access to the upper 9 bits in this case so the non-uniform loading will still be present.

A better way is to use the 68 pin high density connectors for the round cable and use the scheme described above within the connector converter device.

One also needs to consider the TERMPower distribution for this case. The 16 bit path has 4 conductors available for the TERMPower. These 4 lines should be connected together by the 8/16 bit connector converter and passed to the TERMPower lines on the 8 bit side. There is an issue however on the 8 bit side because the single ended and differential TERMPower requirements are different. The single ended uses only one TERMPower line while the differential uses two lines.

The risk is that some older single ended devices may ground one of the pins used for differential TERMPower. If one of these devices is attached it will connect the TERMPower line to ground and disable the entire bus. The simple solution is to connect only the single ended TERMPower line from the 8 bit side to the 4 lines on the 16 bit side. This connector converter will therefore work for both single ended and differential applications.

For the differential case any TERMPower sources on the 8 bit devices will only use one TERMPower line through the connector converter. Since the 8 bit devices are not allowed to have bus termination in this case one does not need to consider this condition.

#### **7.1.1.2. Fast-40 case**

When using fast-40 LVD or HVD the structure described in 7.1.1.1 may be used. In this case the requirements for adding the appropriate capacitive loads to the upper nine bits may become even more critical because there is a fairly stringent requirement for matching the capacitance on the data, parity, and REQ/ACK lines. In general it will require knowledge of the device capacitive loading to know how much capacitance is required so it is expected that the connector conversion device will need to be designed specifically for the LVD device being used.

In practice, however, unless there are many 8 bit LVD devices to be added to the main 16 bit path this caution may be ignored because it is the combined effects of several devices that create the skew problems. One or two 8 bit LVD devices may be added to a 16 bit main path without the need for special, tweaked, connector adapters.

#### **7.1.2. 8 bit main path**

The basic 8 bit main path option is shown in Figure 3. In this case there is no possibility of any 16 bit operation. The 16 bit devices are attached only to their control lines and lower data and parity lines. Since all the lower data and parity lines are connected in every device there is no possibility of the skew problems discussed in 7.1.1. The risks in this configuration are mainly that the upper data and parity bits in the 16 bit devices will not be pulled to the negation state at all times.

If the upper bits are not set to a negated state the 16 bit devices may think that other 16 bit devices are arbitrating for the bus (since the upper data bits are asserted) and will fail. One must provide some electrical means for setting these bits. One simple way for single ended devices is to add a high value resistor (say 100K) to the 5V or 3V supply. This will keep the signals negated and will not significantly increase the device loading if the device is used in a wide application. For differential devices one the +signal line may be grounded through a high value resistor and the - signal line may be connected to the 5V or 3V supply through a high value resistor.




Figure 3 - Mixed width connections using 8 bit main path

7.1.3. Single 16 bit path and single 8 bit path




Figure 4 - Mixed width using a single 8bit and a single 16 bit path

7.1.4. Multiple 8 or 16 bit paths




Figure 5 - Mixed width configuration with two 8 bit paths and one 16 bit path




Figure 6 - Illegal mixed width configuration with two 16 bit paths

## 8. Bus expanders

Bus expanders are elements used for connecting segments together. There are two basic types: simple and bridging. Simple expanders do not occupy a SCSI ID and are intended to be "invisible" to the protocols. Bridging expanders have SCSI ID's on all ports, fully participate in SCSI arbitration and messaging, and are "devices" in the SCSI sense. The following sections describe both types of expander

### 8.1. Simple expanders

The following features are desirable properties of simple bus expanders:

- Minimal propagation delay budget is consumed during arbitration
- No SCSI ID's, no arbitrations can be initiated, no messages originating with the expander can be sent (messages sent from initiators and targets could be read if desired)
- Retransmitted signal timing skew (both delay and hi/lo) are no worse than from a valid SCSI device
- Does not interfere with the REQ/ACK offset count
- Min/Max pulse widths are maintained
- A reset filter is required
- Powered expanders shall retransmit reset assertions from one segment to the other regardless of the state of any other SCSI signals on either side
- Placement of the initiator and targets with respect to the simple expander is arbitrary
- TERMPower is not connected between the segments being coupled
- May or may not need to know the negotiated data phase speed or any other variable property of a transaction (depending on implementation design)
- DIFSENS line is not electrically or logically connected between segments being coupled
- Transmission mode (SE/LVD, etc.) changes on one segment causes the expander to issue a SCSI bus RESET on the other side




Figure 7 - A two segment domain using a single expander circuit




Figure 8 - Three ways to couple bus segments together with expanders

### 8.1.1. Homogeneous type

If an expander has the same type of segment on both sides it is termed a homogeneous expander. The homogeneous expander does not do type conversion (e.g. single ended to HVD).

This kind of expander may be very useful in existing systems where dramatic domain length increases may be achieved simply by inserting a single homogeneous expander in the right place. Such a condition exists, for example in a domain where several single ended devices are connected to a backplane and subsequently to a host adapter. By placing a homogeneous expander near the backplane one creates a short, heavily loaded backplane segment and a point to point segment to the host adapter. According to Table 1 the point to point single ended segment length limit is 20 meters. Without the expander only 1.5 meters including that on the backplane is allowed.

If extended lengths are all that is needed, homogeneous expanders act somewhat similarly to simplex serial line repeaters. They must do a lot more than repeat the signal to work with SCSI but they occupy the same position in a domain drawing as a "repeater"

Homogeneous expanders also provide for isolation of segments from a "main" segment.

### 8.1.2. Heterogeneous types

Expanders that have different bus transmission types on each side are heterogeneous expanders. Using this kind of expander frequently requires planning the domain details before acquiring the devices and expanders, rather than "upgrading" afterwards as with the homogeneous expander. Of course, any expander that implements the universal transceivers can become either homogeneous or heterogeneous.

Heterogeneous expanders are sometimes termed "bus converters".

Heterogeneous expanders may be used in "repeater" modes or in "isolation" modes in the same general way as homogeneous expanders.

### 8.1.3. Domain parameters using simple expanders only

Figure 9 shows some examples of domains that may be built using only simple expanders. The parameters of the domain that must be maintained are discussed in this section. [Ed note: need to consider the domain parameters when using bridging expanders.]]




Figure 9 - Examples of domains using simple expanders

8.1.4. General rules for SCSI domains using only simple expanders

The rules are summarized in section 8.1.4.1 followed by detailed discussion for each in the subsequent sections.

8.1.4.1. Rule summary

Valid SCSI domains must follow these five rules:

1. All bus segments in the domain shall comply with their individual bus segment length limits and other segment related requirements.
2. Any segment between two other segments shall support the highest performance level that can be negotiated between the two other segments. For example two wide LVD Fast 40 segments must not be separated by a segment that does not support both wide and Fast 40. See Table 4 for definition of increasing performance levels. See Figure 10 for examples.
3. The maximum propagation delay between any two devices in the domain shall not exceed 400 ns. For devices that use extremely long times for responding to BUS FREE (the so-called BUS SET DELAY) the one way propagation limit is 300 ns instead of 400 ns (See Figure 11). These extremely long times are caused by devices that use excessive tolerance for their internal clock frequency (like 2x) with resulting sluggish response to asserting their ID's if they wish to participate in arbitration. It is suspected that this condition may exist in old

“fishfinder” applications.

4. The number of addressable devices shall not exceed 16 unless the domain contains LUN bridges (not considered in this document).
5. Acyclic tree architecture must be observed: this is the leaf/branch structure where loops are not allowed.
6. The REQ/ACK offset negotiated between any two devices shall be large enough to ensure that adequate offset and buffering is available to accommodate the round trip time between the devices. For Ultra Fast-20 rates with a maximum domain propagation time this is a minimum offset of 18. See Table 6.

**8.1.4.2. Rule 1**

Rule 1 is explored in detail in section 6.

**8.1.4.3. Rule 2**

Rule 2 relates to intermediate segments which can only exist in domains of at least three segments. The segment between the two other segments is the intermediate segment. The formal ranking of the performance properties for segments is specified in Table 4.

**Table 4 - Performance ranking for intermediate segments**

Performance features listed in order of increasing performance	
Bus segment width	Maximum data phase speed
8 bit	Async
16 bit	slow (“fast” 5) sync
	fast (fast-10) sync
	fast-20 sync
	fast-40 sync
	fast-100 sync

Configurations may exist where it may appear that Rule 2 is satisfied but that actually violates Rule 1. An example of such a configuration is shown in Figure 10.




Figure 10 - Intermediate segments and performance ranking

The configuration in Figure 10 is valid only if the data phase rate is limited to fast-10 for any data phase transactions between segment 1 and segment 2, segment 2 and segment 3 or segment 1 and segment 3. Even though the fast-20 devices in segment 2 are located close to the expanders and the distance between the expanders is small, the segment length is defined by the distance between the terminators - not by the distance to the expander connection or to the devices. The intermediate segment is therefore not fast-20 capable and may not be used for fast-20 transactions between segment 1 and segment 3. (Segment 2 is also not to be used for fast-20 transactions within segment 2.) Fast-20 transactions are allowed between devices in segment 1 or between devices in segment 3.

The intermediate segment in this example will see signals at the higher data rates on the data and parity lines BUT since the devices in the intermediate segment are not participating in the higher data rate transmission and are sitting like good SCSI citizens waiting for the next bus free, reset or other general SCSI phase they are unaffected by the higher speeds.

For multimode segments, any dynamic change of transmission mode (LVD to SE etc.) is considered a fault and the expander is obligated to assert the reset line on the segment opposite the one that experienced the transmission mode change. The expander will detect this state change by sensing the DIFSENS line. This scheme ensures that the initiators on the other segments are aware of the change in transmission mode and can reassess whether this mode change is consistent with the performance requirements for the segments and the overall parameters for the domain before allowing traffic to resume. There is no reliable way to communicate the transmission mode change condition other than using the RESET line. Once RESET is asserted initiators are obliged to renegotiate and should initiate a console level investigation as to the health of the entire domain. (Note that multimode devices are intended to simplify the inventory and part number proliferation issues and are not intended to support dynamic transmission mode changes.)

#### 8.1.4.4. Rule 3

##### 8.1.4.4.1. Effects of Wired-Or glitches

Wired-Or glitches occur when two or more drivers are asserting the same bus line and one ceases to drive the line. This happens frequently during arbitration. This change of driver population causes a redistribution of current in the bus (with resulting voltage glitches) and may cause false detection of BUS FREE. The worst case condition is when two devices near a segment terminator are involved. In this case it requires a full segment length round trip time before the line is again stable (after the device stopped asserting the line). If this condition applies, the round trip time allowed is 400 ns. The one way time is 200 ns.

Conditions exist where one may avoid waiting the entire round trip time by not having a detectable glitch after the initial glitch reaches the far terminator. This document will not describe these conditions but expanders exist that implement this feature. If this condition applies and the conditions described in 8.1.4.4.2 do not apply, the round trip time is 800 ns. The one way time is 400 ns.

This effect of wired-Or glitches applies to the entire domain, not just to individual segments.

##### 8.1.4.4.2. Effects of slow response to BUS FREE

For devices that use extremely long times for responding to BUS FREE (the so-called BUS SET DELAY), the one way propagation limit is 300 ns instead of 400 ns. Figure 11 shows how this 300 ns is derived.

It is generally recommended to ignore this 300 ns limit (since it usually does not apply) and use either 200 or 400 ns for developing specific implementations.



The propagation delay through the differential transceivers of initiators and targets does not need to be separately accounted for if the wired-or glitches cannot propagate through the expander and therefore the effects are confined to single segments. Using “glitch eating” expanders does not allow one segment’s delays to be passed on to the next. This is indeed fortunate since the propagation time through differential transceivers can be significant and would directly subtract from the overall domain budget.

If devices that use the high voltage differential interface are built in compliance with the SCSI standard there will be no difference due to transceiver propagation delay because all SCSI timings are measured at the device connector independent of whether it is a single ended or differential interface. On the other hand, since many protocol chips offer both single direct single ended and differential transceiver options it is very likely that the propagation delay through the differential transceivers will not have been counted in the single segment timing budget (as seen by the protocol chip). This will not matter in most cases if the single segment length is limited to 25 meters since there is a lot of margin built into the 25 meter maximum length. HVD segments that extend the length beyond 25 meters and do not observe the timings at the device connector may produce excessively long wired or glitches as seen by the protocol chips.

8.1.4.4.4. Sample calculations




Figure 12 - Two configurations for domain delay calculations

Figure 12 shows two sample SCSI domain configurations. In case 1 the delay calculations are shown in the figure. For the more complex case 2 one must consider all the possible combinations between any two devices. These calculations are shown in Table 5. The device pair that has the largest combination of expander delay and interconnect delay determines if this configuration meets the 200, 300, or 400 ns requirement.

While this may appear complex, one usually can easily see where the limiting case will be without the rigorous analysis.

**Table 5 - Domain delay calculations**

DEVICE PAIR	PATH BETWEEN DEVICES	EXPANDERS DELAY (ns)	INTERCONNECT DELAY (ns)
1-2	LD13,LD34,LD45,LD52	0	$5.4*(LD13+LD34+LD45+LD52)$
1-3	LD13,E1,LS1	Tds	$5.4*(LD13+LS1)$
1-4	LD13,LD34,E2,LS2	Tds	$5.4*(LD13+LD34+LS2)$
1-5	LD13,LD34,LD45,E3,LS3	Tds	$5.4*(LD13+LD34+LD45+LS3)$
2-3	LD52,LD45,LD34,E1,LS1	Tds	$5.4*(LD52+LD45+LD34+LS1)$
2-4	LD52,LD45,E2,LS2	Tds	$5.4*(LD52+LD45+LS2)$
2-5	LD52,E3,LS3	Tds	$5.4*(LD52+LS3)$
3-4	LS1,E1,LD34,E2,LS2	Tdp	$5.4*(LS1+LD34+LS2)$
3-5	LS1,E1,LD34,LD45,E3,LS3	Tdp	$5.4*(LS1+LD34+LD45+LS3)$
4-5	LS2,E2,LD45,E3,LS3	Tdp	$5.4*(LS2+LD45+LS3)$

**8.1.4.5. Rule 4**

Without special expanders that remap the SCSI ID's to LUN's (LUN bridges 8.2.1.2) there are only a maximum of 16 data bit lines everywhere in the domain and therefore the number of initiators plus the number of targets cannot exceed 16 for the entire domain.

**8.1.4.6. Rule 5**

Since each line must remain responsive to the drivers it is necessary that no lock up conditions exist. Using expanders connected in a loop it is very easy to create conditions where both an expander and a target or initiator is asserting the line. Under these conditions the line will not return to the negated state when the initiator or target releases the line since it will continue to be driven by the expander. The logic state of the line will therefore not change and a lock up condition exists.

Loops are not allowed in any form within a domain. Figure 13 shows some examples of loops. Even if it appears that no lock up condition is possible (in some symmetrical configurations for example) loops are still not allowed because the propagation time variability between components guarantees asymmetry and non-zero lock up risk.




Figure 13 - Examples of illegal loops

**8.1.4.7. Rule 6 (REQ/ACK offset)**

The REQ/ACK offset is the difference between the number of ACK's(REQ's) sent and the number of REQ's(ACK's) received in a synchronous data phase transmission. This offset allows a number of transmissions to be on the domain media at the same time.

The device offset counter is set to zero before the data phase begins. When a REQ is sent or received the offset counter is incremented. When an ACK is sent or received the counter is decremented. After the data phase is completed the offset counter should again be at zero since the number of REQ's and ACK's should be the same. [If this return to zero is not detected it is an indication of very serious problems and should be immediately corrected before using the domain for any critical work.]

When the first ACK(REQ) is sent one must wait a minimum of one round trip time before the first REQ(ACK) can be received from the remote device. This round trip time includes the data processing time at the remote device. ACK's(REQ's) will continue to be issued until the offset counter reaches the maximum REQ/ACK offset level that was negotiated.

If the maximum offset level is reached, the sending device must wait until it sends or receives a decrementing ACK before issuing another REQ. To keep the sending device operating with maximum performance one should never reach the maximum value in the offset counter.

The receiving device should be able to accept up to at least the maximum REQ/ACK offset level of data phase transfers in its buffers.

REQ/ACK offsets do not apply to expanders.

The minimum desirable offset value is given by:

$$OF_{min} = \lceil \{2x \text{ one way domain delay}\} / \{\text{ACK (REQ) period}\} \rceil + \text{processing overhead}$$

Table 6 gives some representative values from the above equation assuming the processing overhead to be 2 ACK(REQ) periods in all cases.

**Table 6 - Minimum REQ/ACK offset levels for max performance**

Domain round trip delay (ns)	Data phase speed	ACK(REQ) period (min)	Minimum REQ/ACK offset to avoid performance degradation (assuming 2 overhead periods in all cases)
100	Fast 10	100	3
200	Fast 10	100	4
300	Fast 10	100	5
400	Fast 10	100	6
500	Fast 10	100	7
600	Fast 10	100	8
700	Fast 10	100	9
800	Fast 10	100	10
100	Fast 20	50	4
200	Fast 20	50	6
300	Fast 20	50	8
400	Fast 20	50	10
500	Fast 20	50	12
600	Fast 20	50	14
700	Fast 20	50	16
800	Fast 20	50	18
100	Fast 40	25	6
200	Fast 40	25	10
300	Fast 40	25	14
400	Fast 40	25	18
500	Fast 40	25	22
600	Fast 40	25	26
700	Fast 40	25	30
800	Fast 40	25	34
100	Fast 100	10	12
200	Fast 100	10	22
300	Fast 100	10	32
400	Fast 100	10	42
500	Fast 100	10	52
600	Fast 100	10	62
700	Fast 100	10	72
800	Fast 100	10	82

**8.2. Bridging expanders**

**8.2.1. General rules for SCSI domains using only bridging expanders**

**8.2.1.1. Expanded device counts in a single domain**

**8.2.1.2. Logical unit bridges**

**8.2.1.2.1. Initiator / target placement**

**8.2.1.2.2. Multi initiator considerations**

**8.2.1.2.3. Reserved ID's on target side**

**8.2.1.2.4. Relationship to Raid models**

**8.2.1.2.5. Impact on SCAM**

**8.2.1.2.6. Target considerations**

**8.2.1.3. Host considerations**

**8.2.1.4. Protocol implications**

**9. Dynamic reconfigurations**

**9.1. Addition and removal of devices**

**9.1.1. Framework of entire process**

## **SCSI HOT PLUGGING**

**THE FIRST SECTION OF THIS DOCUMENT DESCRIBES THE STEPS INVOLVED IN REMOVING AND INSERTING SCSI STORAGE DEVICES ON ACTIVE BUSSES**

**A STRUCTURED APPROACH IS USED WHERE EVERY STEP IN THE PROCESS IS EXAMINED IN DETAIL**

**BOTH THE HARDWARE AND THE SOFTWARE IMPLICATIONS ARE SPECIFIED**

## **SCSI DEVICE HOT PLUGGING**

**THERE ARE TWO END STATES INVOLVED WITH SCSI HOT PLUGGED DEVICES:**

### **1. OPERATIONAL STATE (ES1)**

**FULLY SECURED IN THE ENCLOSURE, FULLY POWERED, FULLY CONNECTED TO ALL SCSI BUS AND GROUND PINS, PHYSICALLY STATIC (EXCEPT FOR HDA), ENABLED TO PARTICIPATE IN ALL ACTIVITIES ALLOWED BY THE DESIGN OF THE DEVICE AND SYSTEM**

### **2. STORED STATE (ES2)**

**UNPOWERED, ELECTRICALLY DISCHARGED, PHYSICALLY STATIC, LOGICALLY UNPROGRAMMED, PHYSICALLY SEPARATED FROM THE BUS AND THE SYSTEM ENCLOSURES THAT CONTAIN THE BUS PORTS**

## **SCSI DEVICE HOT PLUGGING**

**THE HOT PLUGGING PROCESS REQUIRES MOVING SCSI DEVICES FROM ONE END STATE TO THE OTHER WITHOUT INDUCING DAMAGE TO ANY HARDWARE, FIRMWARE OR SOFTWARE COMPONENT OR DAMAGING ANY DATA IN THE SYSTEM OR IN THE DEVICE BEING MOVED**

**THE DEVICE BEING MOVED IS TERMED THE OBJECT DEVICE IN THIS DOCUMENT**

**OBJECT DEVICES ARE OUTGOING OBJECT DEVICES IF THEY ARE GOING FROM ES1 TO ES2**

**OBJECT DEVICES ARE INCOMING OBJECT DEVICES IF THEY ARE GOING FROM ES2 TO ES1**

**AS SOON AS ANY PART OF AN END STATE CONDITION IS NO LONGER VALID THE OBJECT DEVICE IS SAID TO BE IN TRANSITION**

## **SCSI DEVICE HOT PLUGGING**

**THE SCSI BUS THAT DIRECTLY  
CONNECTS TO AN OBJECT DEVICE IS  
TERMED THE MAIN BUS FOR THAT  
DEVICE**

**SOME LEVEL OF DISRUPTION TO THE  
ACTIVITIES ON THE MAIN BUS MUST  
OCCUR REGARDLESS OF THE HOT  
PLUGGING PROCESS USED**

**IN ONE EXTREME HOT PLUGGING  
PROCESS, THE MAIN BUS MUST BE SHUT  
DOWN COMPLETELY FOR PARTS OF THE  
OBJECT DEVICE TRANSITION**

**IN A MINIMALLY DISRUPTIVE HOT  
PLUGGING PROCESS, EXTRA  
COMMUNICATIONS ACROSS THE MAIN  
BUS ARE STILL NECESSARY (TO INFORM  
THE OBJECT DEVICE OR OTHER DEVICES  
ON THE MAIN BUS OF THE IMPENDING  
END STATE CHANGE)**

## SCSI DEVICE HOT PLUGGING

SINCE THE MOST DEMANDING APPLICATIONS REQUIRE MINIMAL DISRUPTION TO THE MAIN BUS ACTIVITIES THE SCSI DEVICE HOT PLUGGING PROCESSES DESCRIBED WILL FOCUS ON THIS CASE

IT WILL BE POINTED OUT HOW ONE MAY MOVE TO MORE DISRUPTIVE HOT PLUGGING PROCESSES IF IMPLEMENTING CERTAIN REQUIREMENTS FOR MINIMALLY DISRUPTIVE PROCESSES IS IMPRACTICAL IN SPECIFIC APPLICATIONS

THE DEGREE OF TOLERABLE MAIN BUS DISRUPTION IS HIGHLY APPLICATION DEPENDENT BUT IT IS VITAL TO HAVE THE DEVICE PROPERTIES, THE APPLICATION REQUIREMENTS, AND THE HOT PLUGGING PROCESS BE CONSISTENT WITH EACH OTHER

## SCSI DEVICE HOT PLUGGING

### FRAMEWORK FOR INCOMING OBJECT DEVICES

STORED END STATE

TRANSITION OUT OF STORAGE CONTAINER

TRANSITION BETWEEN STORAGE CONTAINER AND SERVICE ENCLOSURE

INITIAL TRANSITION INTO SERVICE ENCLOSURE PHYSICAL CONSTRAINTS

TRANSITION TO STATE IMMEDIATELY PRIOR TO MAKING ELECTRICAL CONTACT WITH ANY SERVICE ENCLOSURE ELECTRICAL PINS

TRANSITION FROM NO ELECTRICAL CONTACT TO FULL ELECTRICAL CONTACT

DEVICE INITIALIZATION AND SPIN UP

FIRST DEVICE COMMUNICATIONS

FINAL START UP COMMUNICATIONS

OPERATIONAL END STATE

# SCSI DEVICE HOT PLUGGING

## FRAMEWORK FOR OUTGOING OBJECT DEVICES

**OPERATIONAL END STATE**

COMMUNICATIONS TO BEGIN REMOVAL FROM THE ACTIVE BUS  
ALL BUS TRAFFIC TO OUTGOING OBJECT DEVICE CEASED  
DEVICE SPIN DOWN

TRANSITION FROM FULL ELECTRICAL CONTACT TO NO ELECTRICAL CONTACT

TRANSITION FROM STATE IMMEDIATELY AFTER MAKING ELECTRICAL DISCONNECT TO READY FOR FINAL REMOVAL FROM SERVICE ENCLOSURE

FINAL REMOVAL FROM SERVICE ENCLOSURE PHYSICAL CONSTRAINTS

TRANSITION BETWEEN SERVICE ENCLOSURE AND STORAGE CONTAINER

TRANSITION INTO STORAGE CONTAINER

**STORED END STATE**

### 9.1.2. Electrical considerations

Hot plugging details:

This section describes details of the mechanics and issues that operate during the insertion and removal of devices when using the SCA-2 connector system

#### 9.1.2.1. Insertion

Figure 14 shows the relative contact positions of the advanced grounding, long and short contacts as specified for the SCA-2 connector system in stages 0 thru 3 of the insertion process. Figure 15 shows stages 4 thru 7. Each stage may last for many milliseconds or seconds – not predictable.




Figure 14 - Stages 0 thru 3 for the insertion process

Stage 0 - No contacts mated (Figure 14)

Issues, effects, comments

Mechanical stresses, vibration, electrical activity limited to possible enclosure to device “skin” ESD for devices with electrically exposed “skins”.

Stage 1 - First advanced grounding contact electrical activity (Figure 14)

Issues, effects, comments

ESD / ground potential equalization

White noise radiation into device cavity from metal to metal discharge

Ground loop currents initiate if any power source or power ground is attached to the incoming device through a cable

Stage 2 - Wiping of advanced grounding contacts prior to first long contact electrical activity (Figure 14)

Issues, effects, comments

Sustained ground loop currents between incoming device and enclosure ground (if any) freely flowing / possibly interrupted by the wiping action

Stage 3 - AGC continues to wipe, first long contact electrical activity (Figure 14)

Issues, effects, comments

Stage 2 issues still in effect for all cases

Case 1: first long contact to mate is a device ground (Figure 14)

No effect, no arcing, least disruptive case

Case 2: first long power contact to mate is a 12 V power contact (Figure 14)

Arcing / white radiation at long 12V power contact during device decoupling capacitor charging

12V power current is returned only through the ACG contacts until the first long contact ground pin mates after which the return current is shared between the AGC and the long contact ground pin.

Note that if the AGC contact is not mated prior to this event then the long 12V power contact will perform the Stage 1 ESD function and will transfer the stage 3 arcing to the next pin that mates.

If the next contact to mate is the long 5V power contact (and still assuming that the AGC did not mate) then the voltage on the device ground will assume the value dictated by the capacitive division on the device between 12V and 5V – for the example where this value is 8.5V (half the difference between 12V and 5V) the 5V circuitry could see minus 3.5V until the device ground or the AGC contacts mate. This condition can also forward bias (possibly destructively) any diodes in the 5V circuitry that happen to be connected to the device ground.


Case 3: first long power contact to mate is a 5 V power contact (Figure 14)

Arcing / white radiation at long 5V power contact during device decoupling capacitor charging

5V power current is returned through the ACG contacts until the first long contact ground pin mates

Note that if the AGC contact is not mated prior to this event the long 5V power contact will perform the Stage 1 ESD function and will transfer the stage 3 arcing to the next pin that mates.

If the next pin to mate is the long 12V power contact (and still assuming that the AGC did not mate) then the voltage on the device ground will assume the value dictated by the capacitive division on the device between 12V and 5V – for the example where this value is 8.5V (half the difference between 12V and 5V) the 5V circuitry could see minus 3.5V until the device ground or the AGC contacts mate. This condition can also forward bias (possibly destructively) any diodes in the 5V circuitry that happen to be connected to the device ground.



**Figure 15 - Stages 4 thru 7 for the insertion process**

Stage 4 - AGC continues to wipe, all long contacts mated and wiping (Figure 15)

Issues, effects, comments

Stage 2 issues still in effect

Possible power loading transients due to wiping action

Power decoupling capacitors charging

Logic becoming powered (non necessarily reliable in this stage)

All SCSI pins set to high impedance state (should always be in this state during all parts of stage 4)

Stage 5 - AGC continues to wipe, all long contacts mated and wiping, first short contact electrical activity (Figure 15)

Issues, effects, comments

Stages 2 and 4 issues still in effect

Low power transients seen on active SCSI lines of operating bus segment due to charging of device pins - very little radiation due to low power - no detectable glitches expected if the ACG contacts operate properly and the SCSI pins remain in the high impedance state as required

Arbitrary logic patterns presented to incoming device receiver as different SCSI signal contacts begin to mate - receivers must NOT operate on any inputs in this stage

Additional power contacts mate providing beginnings of stable power for logic and other electronics - should be very low arcing due to precharge from long power pins

No reliable sequencing between SCSI signals and power

Stage 6 - All contacts mated and wiping (Figure 15)

Issues, effects, comments

Stages 2 and 4 issues still in effect

Logic inputs stabilize

Power stabilizes

No reliable detection that all pins are in Stage 6 from connector behavior alone

No device operation should be attempted in this stage

Stage 7 - All contacts fully seated (Figure 15)

Issues, effects, comments

Stages 2, 4, and 6 issues cease

All physical transient effects completed – physical insertion process completed except for possible mechanical latching of device.

**9.1.2.2. Removal**

**9.1.3. Logic input states during transitions**

In sections 9.1.2.1 and 9.1.2.2 it was noted that conditions exist where the input logic state is not defined and may have nearly arbitrary values. This sections provides more detail on the required actions of receivers in this state. [details to be added].

**9.1.4. Protocol implications**

**9.2. Addition and removal of bus segments**

Bus segments may be added or removed from an active domain under certain conditions. This section describes those conditions. The segment being removed / added is termed the object segment in this document.

Only bus segments that have a single expander attached may be considered for dynamic removal/addition. Segments between other segments must be maintained to allow the other segments to continue to communicate.

The general topology of a section of a domain containing a separable segment is shown in Figure 16.



The choice of which option to use is dictated by system considerations such as the existence and accessibility of the connectors, separate power controls to the expander, and the use of the expander to supply TERMPWR to the segments.

The object segment addition process proceeds as follows:

All devices (except the expander) on the object segment cease all object segment driving activity. This includes any “background polling” activity. The expander may drive the object segment as a result of the process of connecting the expander to the active segment.

The basic requirement is that the signals at the active segment connector remain in the high impedance state until the devices on the object segment have been initialized (see section xxxx).

The segment addition process is essentially the reverse of the removal process using one of the following.

1. the object segment is assembled to the expander and the unpowered expander is then connected to the active bus segment connector.. The object segment TERMPWR is turned on, the expander is next powered on and the object segment devices are initialized.
2. the unpowered expander is connected to the active bus segment without the object segment attached. The object segment is then connected to the expander, object segment TERMPWR is applied, and the expander is powered on and the object segment devices are initialized.
3. the expander is attached to the active bus segment connector and then powered on (if not already powered on before the attachment. The TERMPWR is then applied to the object segment and the object segment connector is mated. Devices on the object segment are then initialized.

All options require the expander to power cycle without driving the active bus segment.

Option 3 requires the TERMPWR pin to mate before any signal or DIFFSENS pin if TERMPWR is supplied to the object segment by the expander.

## **10. Topologies and configuration rules for dynamically reconfigurable systems**

### **10.1. Initiator placement**

### **10.2. Redundant paths**

### **10.3. Initialization**

This section is needed to support the addition and removal of bus segments.

### **10.4. Power considerations**

SCSI consumes power in two ways: transceivers and terminators. Section 11 explores the issues and opportunities for the supply of power to the terminators. This section deals with the power implications when system reconfigurations are done.

## **11. Terminator power distribution**

SCSI provides the TERMPWR lines in the cables for distribution of TERMPWR from the TERMPWR sources to the terminators. Beginning with SPI-2 it is no longer required to use these lines as the only means to power terminators. The easiest way to deal with TERMPWR distribution is to provide each terminator with its own local TERMPWR

source thereby obviating the need for distribution. This section deals with the case where the TERMPWR lines are used to supply power to the terminators.

**11.1. Wire effects**

The options and complexity of TERMPWR distribution have grown fairly dramatically in the last few years. This is caused by the advent of wide SCSI, low dropout regulators for active termination, demand for smaller cables with smaller wire gauge, longer busses, and devices operating from low voltage supplies. The most important of these are the low dropout regulators and the low voltage sources.

The most demanding case for TERMPWR distribution is when the TERMPWR source is at one end and the terminator at the remote end must get its power only through the TERMPWR lines in the bus. Fortunately the TERMPWR lines only need to supply the current for a single terminator. One can calculate how long the bus can be for a variety of conditions under these worst case conditions.

No allowance is made in these calculations for ground shift between the TERMPWR source and the remote terminator. See section 12 for discussions of ground distribution. If there is more than a few millivolts of ground shift one will need to reduce the lengths even more (except in the extremely rare case where the ground shift is stable and favors the current flow to the terminator).

The TERMPWR lines only need to supply power to the lines that are asserted. For 8 bit SCSI the maximum number of lines that can be asserted at any one time is 12 and for 16 bit SCSI (P cable) the maximum number is 21). This also reduces the amount of current in the TERMPWR lines.

Bus segment length limited by TERMPWR distribution is the longest length that can deliver the minimum voltage needed by the terminator when the maximum number of lines are asserted. The voltage needed by the terminator depends on the transmission mode and the kind of terminator being used.

The options considered for TERMPWR conductors are 1, 2, or 4 conductors of 28, 30 , or 32 gauge wire. Each connector will add some resistance (assumed to be 25 milliohms each mated pair). The options for minimum source voltage delivered to the TERMPWR lines are 2.8, 2.94, and 4.25 volts. These values are derived as shown in Table 7. The 4 conductor option is only used when assuming 21 asserted lines for the wide case.

**Table 7 - TERMPWR source voltages**

TERMPWR SOURCE	Power supply voltage (minimum)	Forward voltage drop across isolating component	Minimum delivered TERMPWR voltage to the TERMPWR lines
5V a.c. supply (10%)	4.5	0.25	4.25
3.3V a.c. supply (5%)	3.135	0.2	2.935 (2.94)
3.3V battery	3.0	0.2	2.80

**11.1.1. Single ended**

The SPI standard requires that single ended terminators source current to the signal line whenever the voltage on that line falls below 2.5 volts. This is a minimal condition that is used in the calculations in this section. It is clear that this assumption does not produce as large a negated signal as normally found with the linear alternative 2 SCSI-2 active (regulated) terminator (2.85 volts). On the other hand, since the negated signal is not as large, a low assertion level is not as difficult to attain. In the long cables where the TERMPWR distribution may limit the length, the assertion level is one of the more difficult features to achieve.

These calculations assume only regulated, linear terminators.

Regulators are used between the TERMPWR lines and the internal termination circuitry to isolate the effects of noise and source voltage level variations on the TERMPWR lines from the signal lines. Recently regulators have become available that require as little as 0.2 V difference to achieve regulation. More commonly, approximately 1.2 to 1.5 volt is required and the normal expectation is that single ended linear regulated terminators need 4.0 volts to stay in regulation. The calculations consider the two extreme cases where (1) the best regulators and the lowest delivered voltage combine to require 2.7 V delivered to the terminator and (2) the lesser regulators and the desire for a bit higher than 2.5 V combine to require 4.0 volts delivered to the terminator. The best TERMPWR distribution conditions occur when a 5V supply is used with a 2.7 V terminator.

Table 8 considers two cases for the number of connectors used between the TERMPWR source and the terminator. It is not common to have less than approximately 3 connectors and it takes a fairly complex system to have 15 connectors in the same segment so these were chosen to bound the calculations. For systems with intermediate numbers of connectors a linear interpolation is reasonable.

The range of useful length is extremely large ranging from not working at all to over 170 feet. The present SCSI standards are written assuming the case of 3 connectors, a 4.25V source and a 4.0 V terminator with a single 28 gauge TERMPWR line. This gives the 10.8 feet in Table 8.

The two conductor case represents using both TERMPWR lines for single ended TERMPWR distribution as specified for the narrow differential cases. This requires connecting both lines to the same pin normally used for supplying the terminator BEFORE getting to the terminator. The connection may be done in the cable assembly backshell, on the printed circuit board between the cable assembly and the terminator or at the terminator pins. Single ended terminators do NOT connect these lines together inside and the benefits of a double TERMPWR distribution path will not happen if the external connection is not done. Similar comments apply at the source side.

**Table 8 - TERMPWR single ended bus segment length limits**

NARROW - 15 CONNECTORS							
SOURCE	TERM	1-28	1-30	1-32	2-28	2-30	2-32
2.8 V	2.7 V	--	--	--	--	--	--
2.94 V	2.7 V	5.3	3.2	2	10.6	6.4	4
4.25 V	2.7 V	68.4	41.1	25.7	136.9	82.1	51.3
4.25 V	4.0 V	5.8	3.5	2.17	11.6	7	4.4
NARROW - 3 CONNECTORS							
2.8 V	2.7 V	3.6	2.1	1.3	7.1	4.3	2.7
2.94 V	2.7 V	10.3	6.2	3.9	20.6	12.4	7.7
4.25 V	2.7 V	73.4	44.1	27.5	146.9	88.1	55.1
4.25 V	4.0 V	10.8	6.5	4.1	21.6	13	8.1
WIDE - 15 CONNECTORS							
		4-28	4-30	4-32			
2.8 V	2.7 V	5	3	1.86		f	
2.94 V	2.7 V	20.7	12.4	7.8			
4.25 V	2.7 V	167.7	100.6	62.9			
4.25 V	4.0 V	21.8	13.1	8.2			
WIDE - 3 CONNECTORS							
2.8 V	2.7 V	10	6	3.7			
2.94 V	2.7 V	25.7	15.4	9.6			
4.25 V	2.7 V	172.7	103.6	64.8			
4.25 V	4.0 V	26.8	16.1	10.1			
ALL LENGTHS IN FEET				-- = DOES NOT WORK			

Clearly there are a wide variety lengths possible and a large number of traps. For example, 3.3 volt battery powered devices simply cannot run narrow SCSI at the lower end of the battery voltage spec.

Careful study of Table 8 is recommended for all implementations of single ended SCSI.

### **11.1.2. Low voltage differential (LVD)**

LVD terminators require voltages no lower than 3.0 V and current of at least 0.5 A per wide terminator. This is similar to the 2.7V / wide case in Table 8 since the voltage requirement is 10% higher but the current is slightly more than 10% lower.

### **11.1.3. Multimode SE/LVD**

For this case the terminators require voltages no lower than 3.0 V (if the SE mode uses regulators that can use 3.0V ) and current of at least 0.65 A per wide terminator. If the SE mode requires 4.0 V the voltage requirement goes to 4.0V. A separate table is needed to show this case (To be done in the future)

### **11.1.4. High voltage differential**

The HVD case requires at least 4.0 V and 1.0 A delivered to each wide terminator. This is by far the most demanding case for TERMPWR distribution because the current requirement is approximately twice that for the SE or LVD versions. A separate table is needed to show this case (To be done in the future).

## **11.2. Mixed power configurations**

This section considers the issues involved when different kinds of TERMPWR sources are used in the same segment.

### **11.2.1. High voltage / Low voltage**

### **11.2.2. Power on / Power off segments**

Expanders shall propagate reset under all powered up conditions. This allows the bus to be reset due to catastrophic events on one side that could lock up the expander. [should be added to expander requirements section]

## **11.3. Terminator considerations**

## **11.4. TERMPWR source placement**

## **12. Grounding and ground distribution**

This section explores the not-so-obvious issues with achieving grounding in SCSI systems. When operating under extended configurations the effects of improper grounding are more likely to be manifested

The objective of a good grounding system is to minimize the noise voltage generated by currents from circuits flowing through a common ground impedance and to avoid creating ground loops or to keep them as small as possible. A good ground system will improve signal quality while reducing electromagnetic emissions. This section provides guidance on the proper usage of the lines presently identified as “grounds” in the SCSI standards.

There are four types of “grounds” identified in the SCSI physical interface:

- logic grounds
- d.c. power grounds
- signal return lines
- shield ground

The logic ground lines are used to connect the logic grounds within all devices on the bus. They are connected to the non-signal return ground lines in the SCSI cable.

The d. c. power grounds (SCA-2 connector only) are used for connecting device power grounds to the local enclosure power ground. Unlike the logic grounds, they are confined to internal applications only and may not be exported directly onto an external SCSI cable.

The signal return lines are associated with the single ended signals. Every single ended signal (except for Term Power) is paired with a ground line. The signal return is the return path for the signal circuit.

The shield ground provides the EMC integrity between external enclosures.

#### **12.1. Single ended systems**

In the single ended systems the signal return lines shall be connected to the logic ground of the chip containing the SCSI transceivers in SCSI devices and to the signal ground within the terminators.

The logic ground lines should be tied to the logic ground plane in each SCSI device as close as possible to the device SCSI connector.

The d.c. power grounds (SCA-2 connector) shall not be directly connected to any line in the SCSI cable that leaves the enclosure containing the device with the SCA-2 connector.

#### **12.2. Differential systems**

HVD and LVD systems shall have the logic ground lines connected to the logic ground plane in each SCSI device as close to the connector as possible.

The d.c. power grounds (SCA-2 connector) shall not be directly connected to any line in the SCSI cable that leaves the enclosure containing the device with the SCA-2 connector.




Figure 17 - Examples of various ground points

**12.3. Shield connections**

The shield shall have a maximum d. c. resistance of 30 milliohms between the cable shield on the cable media and the enclosure wall. It is recommended that the cable have a 360 degree termination around the connector. External connectors shall have a low-impedance (at all frequencies relevant to the system) bond between the cable shield and the chassis. Cable shields shall not be directly connected to logic ground within the SCSI device – such connections, if any, shall be made indirectly through grounding scheme used within the device enclosure.




Figure 18 - Shield connection details

**12.4. System considerations:**

All SCSI systems are direct coupled and are therefore affected by ground currents and voltages. All enclosures within the same SCSI bus segment should acquire their power from the same power distribution panel within the building. If possible, they should all be connected to the same power outlet.

The shield conductors and the internal cable "ground" lines all help to maintain the same ground voltage throughout the segment but they are frequently not enough to compensate for faulty system power distribution or for ground voltages built up between different power distribution panels in a building.

**13. References and tables**

**13.1. SFF-8017 reference**

**13.1.1. Wiring tables**

TABLES

TABLE 5-1	REFERENCE TO SPECIFIED COMBINATIONS	10
TABLE 6-1	SINGLE ENDED: CONTACT ASSIGNMENTS FOR SCSI-2 A-CABLE	12
TABLE 6-2	DIFFERENTIAL: CONTACT ASSIGNMENTS FOR SCSI-2 A-CABLE	13

TABLE 6-3	SINGLE ENDED: CONNECTOR CONTACTS FOR SCSI-3 P-CABLE	14
TABLE 6-4	DIFFERENTIAL: CONNECTOR CONTACTS FOR SCSI-3 P-CABLE	15
TABLE 6-5	SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8003 A-CABLE	16
TABLE 6-6	DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8003 A-CABLE	17
TABLE 6-7	SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8003 P-CABLE	18
TABLE 6-8	DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8003 P-CABLE	19
TABLE 6-9	SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8015 SCA	20
TABLE 6-10	DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8015 SCA	21
TABLE 6-11	SINGLE ENDED: 68-PIN SCSI-3 CONNECTOR & SCSI-2 A-CABLE	22
TABLE 6-12	DIFFERENTIAL: 68-PIN SCSI-3 CONNECTOR & SCSI-2 A-CABLE	23
TABLE 6-13	SINGLE ENDED: 50-PIN SFF-8003 CONNECTOR & SCSI-2 A-CABLE	24
TABLE 6-14	DIFFERENTIAL: 50-PIN SFF-8003 CONNECTOR & SCSI-2 A-CABLE	25
TABLE 6-15	SINGLE ENDED: 68-PIN SFF-8003 CONNECTOR & SCSI-3 P-CABLE	26
TABLE 6-16	DIFFERENTIAL: 68-PIN SFF-8003 CONNECTOR & SCSI-3 P-CABLE	27
TABLE 6-17	SINGLE ENDED: 68-PIN SFF-8003 CONNECTOR & SCSI-2 A-CABLE	28
TABLE 6-18	DIFFERENTIAL: 68-PIN SFF-8003 CONNECTOR & SCSI-2 A-CABLE	29
TABLE 6-19	SINGLE ENDED: 80-PIN SFF-8015 CONNECTOR TO SCSI-2 A-CABLE	30
TABLE 6-20	SINGLE ENDED: 80-PIN SFF-8015 CONNECTOR TO SCSI-3 P-CABLE	31
TABLE 6-21	DIFFERENTIAL: 80-PIN SFF-8015 CONNECTOR TO SCSI-2 A-CABLE	32
TABLE 6-22	DIFFERENTIAL: 80-PIN SFF-8015 CONNECTOR TO SCSI-3 P-CABLE	33
TABLE 6-23	SINGLE ENDED: 50-PIN SCSI-2 CONNECTOR TO SCSI-3 P-CABLE	34
TABLE 6-24	DIFFERENTIAL: 50-PIN SCSI-2 CONNECTOR TO SCSI-3 P-CABLE	35
TABLE 6-25	SINGLE ENDED: 50-PIN SFF-8003 CONNECTOR TO SCSI-3 P-CABLE	36
TABLE 6-26	DIFFERENTIAL: 50-PIN SFF-8003 CONNECTOR TO SCSI-3 P-CABLE	37
TABLE 6-27	SINGLE ENDED: 68-PIN SCSI-3 CONNECTOR TO 2 SCSI-2 A-CABLE	38

## 1. Scope

This specification defines the SCSI wiring rules for a wide variety of interconnects that are possible using the presently available connectors described in standards and SFF specifications.

Such connections are desirable in mixed width SCSI systems e.g. using the 68-pin connector in anticipation of connecting to wide SCSI systems in the future. Other applications included in this specification described the wiring for backplane attached devices.

## 3. General Description

The variety of SCSI (Small Computer System Interface) cabling alternatives means that integrators are facing the need to connect a 16-bit SCSI-3 P-cable (High Density 68-pin) device or connector and an 8-bit A-cable device or connector.

One relatively inexpensive way to make this connection is via a 50-conductor adapter cable which has a SCSI-3 68-pin high density connector on one end and a SCSI-2 50-pin connector (either high or low density) on the other end.

The SCSI-3 Physical Interface standard (X3T9.2/0855D) specifies how to connect an A-cable to a 16-bit P-cable but does not describe how to wire a 68-pin connector if it is being used only for an A-cable connection.

This document specifies the wiring of the 68-pin cable connector in this type of application. Failure to follow this specification can result in TERMPWR (Termination Power) shorts and one likely result is a device failure.

The 50-pin connector plug on the adapter cable is wired according to the specifications in X3.131R-199x for SCSI-2, but follows the SCSI-3 wiring requirements on pair placement in round cables (if round cables are being used).

The 68-pin connector receptacle is either wired as specified in SCSI-3 if it is a 16-bit P-cable device or as specified in this document if it is an A-cable device.

There is an issue with electrical termination of the 9 unused signal pairs if a 16-bit P-cable wiring is used on the receptacle side of the 68-pin connector. This is especially important if 16-bit devices are connected to an 8-bit bus, since the 9 lines will float to an asserted state for single ended and to an indeterminate state for differential. This electrical condition will prevent a 16-bit device from working even if it is only doing 8-bit transfers, unless wired according to this Specification.

## 5. Wiring Rules

### 5.1 Considerations

This specification contains the SCSI wiring rules for a wide range of interconnects that are possible using the presently available standards for SCSI connectors (both in X3T9.2/X3T10 and SFF) i.e. the wiring rules for A-cables and P-cables when used with mixed width and SFF Committee-specified connections.

Connections beyond the simple A-cable, P-cable, and A-cable to P-cable have become possible and likely since the creation of the original specification for the SCSI A-cable in the SCSI-2 specification and the original specification for the SCSI P-cable in the draft SPI (SCSI-3 Parallel Interface) standard. This specification is a comprehensive collection of wiring tables for the new connections that may now exist. There is no support for the SCSI-2 B-cable in this specification.

The starting point is the A-cable and P-cable connections as referenced above in the SCSI-2 and SCSI-3 standards.

The term A-cable in this specification means a 50-conductor bus whose lines are functioning as defined in the SCSI-2 standard.

The term P-cable in this specification means a 68-conductor bus whose lines are functioning as defined in the SCSI-3 SPI standard. Generally the function of the lines is determined by the devices connected to the bus. This specification assumes that the SCSI-2 or SCSI-3 standard devices take precedence over these bus functions.

Line functions that are peculiar to an SFF device are not continued into a standard A-cable or P-cable although these special functions may exist in

limited domains (within a notebook computer for example).

This specification does not directly consider the cases where only different SFF connectors may be connected to the same bus. One may assume the bus is functioning as a standard A-cable or P-cable and safely use the wiring tables

but since there would be no standard A-cable or P-cable devices to provide the line functions this could lead to inefficient implementations.

The wiring tables specify how to connect either the A-cable or P-cable to the connections listed below.

The two (and only two) terminators on the bus define the ends of the bus. The electrical path forming continuity between these terminators is the bus path. Any other electrical path is a stub path.

There are two basic kinds of connection described: stubbing and bussing.

A stubbing connection occurs when breaking the connection does NOT cause loss of bus continuity from terminator to terminator. A stubbing connection cannot involve any bus termination.

A bussing connection occurs when breaking the connection does cause loss of bus continuity from terminator to terminator. A bussing connection must directly involve bus termination. This is specified in the tables where appropriate.

There are a family of connectors that must be considered. Whether these connectors are high or low density or are shielded or not does not affect these wiring tables. Note however that the 50-pin SCSI-2 connections have different pin numbers depending on the connector contact number set being used.

The low density unshielded SCSI-2 50-pin connector will use connector contact number Set 1. All others use connector contact number Set 2. This translation between Set 1 and Set 2 is shown in Table 1. All other references in this specification to the A-cable connector pins will use Set 2 or simply the cable conductor number.

The combination of a connector with a specific wiring pattern is termed a connection in this document.

Connections considered in this specification:

- 50-pin SCSI-2
- 68-pin SCSI-3
- 80-pin SCA (Single Connector Attachment) SFF-8015
- 50-pin SFF-8003
- 68-pin SFF-8003

Also included in this specification are differential pinouts for the SCA and

SFF connectors since these are not defined in the source documents.

In space confined situations, such as with PC option panels, one may pass two single ended A-cables through a single 68-pin SCSI-3 connector. This is done by commoning grounds and sacrificing three of the reserved lines. The wiring specification for this connection is also contained in this document.

## 5.2 Intermix Cases Covered

### 5.2.1 Single Ended

- Base SCSI-2 A-cable connection (device side)
- Base SCSI-3 P-cable connection (device side)
- Base SCA A-cable connection (device side)
- Base SCA P-cable connection (device side)
- Base SFF A-cable connection (device side)
- Base SFF P-cable connection (device side)
  
- A-cable with a 68-pin SCSI-3 stubbing connection
- A-cable with a 68-pin SCSI-3 bussing connection
- P-cable with a 50-pin SCSI-2 stubbing connection
- P-cable with a 50-pin SCSI-2 bussing connection
- A-cable with a stubbing 80-pin SCI connection
- A-cable with a bussing 80-pin SCI connection
- P-cable with a stubbing 80-pin SCI connection
- P-cable with a bussing 80-pin SCI connection
- A-cable with a stubbing SFF 50-pin connection
- A-cable with a bussing SFF 50-pin connection
- A-cable with a stubbing SFF 68-pin connection
- A-cable with a bussing SFF 68-pin connection
- P-cable with a stubbing SFF 68-pin connection
- P-cable with a bussing SFF 68-pin connection
- P-cable with a stubbing SFF 50-pin connection
- P-cable with a bussing SFF 50-pin connection
- 2 A-cables with a single 68-pin SCSI-3 stubbing connection
- 2 A-cables with a single 68-pin SCSI-3 bussing connection

### 5.2.2 Differential

- Base SCSI-2 A-cable connection (device side)
- Base SCSI-3 P-cable connection (device side)
- Base SCA A-cable connection (device side)
- Base SCA P-cable connection (device side)
- Base SFF A-cable connection (device side)
- Base SFF P-cable connection (device side)
  
- A-cable with a 68-pin SCSI-3 stubbing connection
- A-cable with a 68-pin SCSI-3 bussing connection
- P-cable with a 50-pin SCSI-2 stubbing connection
- P-cable with a 50-pin SCSI-2 bussing connection
- A-cable with a stubbing 80-pin SCI connection
- A-cable with a bussing 80-pin SCI connection
- P-cable with a stubbing 80-pin SCI connection
- P-cable with a bussing 80-pin SCI connection
- A-cable with a stubbing SFF 50-pin connection
- A-cable with a bussing SFF 50-pin connection
- A-cable with a stubbing SFF 68-pin connection
- A-cable with a bussing SFF 68-pin connection
- P-cable with a stubbing SFF 68-pin connection
- P-cable with a bussing SFF 68-pin connection
- P-cable with a stubbing SFF 50-pin connection
- P-cable with a bussing SFF 50-pin connection

## 5.3 Cross Reference

Table 5-1 identifies the combinations which are specified in Clause 6.

TABLE 5-1 REFERENCE TO SPECIFIED COMBINATIONS

	50-pin SCSI-2	68-pin SCSI-3	80-pin SFF-8015	50-pin SFF-8003	68-pin SFF-8003
Basic Single Ended Cable Pinout	6- 1	6- 3	6- 9	6- 5	6- 7
Basic Differential Cable Pinout	6- 2	6- 4	6- 10	6- 6	6- 8
A-Cable Single Ended Cable Bussing	6- 1	6- 11	N/A	6- 13	6- 17
A-Cable Single Ended Cable Stubbing	6-1	6-11	6-19	6-13	6-17
A-Cable Differential Cable Bussing	6-2	6-12	N/A	6-14	6-18
A-Cable Differential Cable Stubbing	6-2	6-12	6-21	6-14	6-18
P-Cable Single Ended Cable Bussing	N/A	6-3	N/A	N/A	6-15
P-Cable Single Ended Cable Stubbing	6-23	6-3	6-20	6-25	6-15
P-Cable Differential Cable Bussing	N/A	6-4	N/A	N/A	6-16
P-Cable Differential Cable Stubbing	6-23	6-4	6-22	6-26	6-16
Dual A-Cable Single Ended Cable Bussing		6-27			
Dual A-Cable Single Ended Cable Stubbing		6-27			

## 5.4 Bus Termination

### 5.4.1 General Applications

For 16-bit devices (devices with a 68-pin SCSI-3 connector) onboard bus termination may be accomplished:

- in the manner specified in the SPI document if the device is providing bus termination for the entire 68-pin connector (end of bus device applications only).
- in the manner specified in the SPI document if the device is providing bus termination for the upper data and parity bits only (end of P-cable bus segment device applications only)

### 5.4.2 Specific Precautions

In some application for 16-bit devices special considerations must be taken to ensure proper termination of the unused signals is accomplished.

- Electronics suitable for setting the upper data and parity bit signals to the deasserted (negated) state may be connected on the device board in the case where the 16-bit device is connected only to an 8-bit path (such as when using a cable assembly as specified in Section 5). If the unused pins are not terminated or asserted on board, the required negations or terminations have to be provided in the cable assembly.

If some means of electronic termination is not implemented on the unused lines, the upper data and parity bits may "float" to what appears to be an asserted state and cause device or system operational problems. The unused lines do not have to meet the electrical requirements for SCSI bus termination and may be built of resistors. Resistors of at least 100K ohms should be used to avoid loading the bus.

- high value pull up resistors for single ended.
- high value resistors in a totem pole for differential.

It is recommended that resistors or some alternative form of electronic termination be implemented in all 16-bit devices.

## 5.5 Rack Mount Considerations

Connectors such as the SFF-8015 SCA (Single Connector Attach) are not designed to accept cables, but there are considerations such as cabling between two cabinets via an SCA connector and connecting a device with a SCA connector to a backplane that also has standard SCSI connectors to the outside world.

Such bussing connections are not generally allowed due to the lack of continuity in several key signals e.g. TERMPWR, RESERVED and some GROUND lines. If there is a terminator on an SCA device (thereby making it a bussing connection) AND there is a local source of TERMPWR for the terminator the connections can be followed if the Reserved lines are not used. NOTE: Such a configuration is not strictly 'legal' since TERMPWR should only be supplied to terminators from the TERMPWR signal (as defined in SCSI-2 and SCSI-3 SPI).

TABLE 6-1 SINGLE ENDED: CONTACT ASSIGNMENTS FOR SCSI-2 A-CABLE

Connector Contacts and Signal Names			Cable Conductor Numbers		Connector Contacts and Signal Names		
Set 2 Set 1					Set 1 Set 2		
1	1	GROUND	1	2	-DB(0)	2	26
2	3	GROUND	3	4	-DB(1)	4	27
3	5	GROUND	5	6	-DB(2)	6	28
4	7	GROUND	7	8	-DB(3)	8	29
5	9	GROUND	9	10	-DB(4)	10	30
6	11	GROUND	11	12	-DB(5)	12	31
7	13	GROUND	13	14	-DB(6)	14	32
8	15	GROUND	15	16	-DB(7)	16	33
9	17	GROUND	17	18	-DB(P)	18	34
10	19	GROUND	19	20	GROUND	20	35
11	21	GROUND	21	22	GROUND	22	36
12	23	RESERVED	23	24	RESERVED	24	37
13	25	OPEN	25	26	TERMPWR	26	38
14	27	RESERVED	27	28	RESERVED	28	39
15	29	GROUND	29	30	GROUND	30	40
16	31	GROUND	31	32	-ATN	32	41
17	33	GROUND	33	34	GROUND	34	42
18	35	GROUND	35	36	-BSY	36	43
19	37	GROUND	37	38	-ACK	38	44
20	39	GROUND	39	40	-RST	40	45
21	41	GROUND	41	42	-MSG	42	46
22	43	GROUND	43	44	-SEL	44	47
23	45	GROUND	45	46	-C/D	46	48
24	47	GROUND	47	48	-REQ	48	49
25	49	GROUND	49	50	-I/O	50	50

- NOTES: 1) The conductor number refers to the conductor position when using 0.050" centerline flat ribbon cable with a low-density connector or when using 0.025" centerline flat ribbon cable with a high-density connector. Other cable types may be used to implement equivalent contact assignments.
- 3) Two sets of contact assignments are shown. Set 1 applies to the low density internal device connector only. Set 2 applies to all other connector styles.

TABLE 6-2 DIFFERENTIAL: CONTACT ASSIGNMENTS FOR SCSI-2 A-CABLE

Connector Contacts and Signal Names		Cable Conductor Numbers	Connector Contacts and Signal Names				
Set 2	Set 1		Set 1	Set 2	Set 2		
1	1	GROUND	1	2	GROUND	2	26
2	3	+DB(0)	3	4	-DB(0)	4	27
3	5	+DB(1)	5	6	-DB(1)	6	28
4	7	+DB(2)	7	8	-DB(2)	8	29
5	9	+DB(3)	9	10	-DB(3)	10	30
6	11	+DB(4)	11	12	-DB(4)	12	31
7	13	+DB(5)	13	14	-DB(5)	14	32
8	15	+DB(6)	15	16	-DB(6)	16	33
9	17	+DB(7)	17	18	-DB(7)	18	34
10	19	+DB(P)	19	20	-DB(P)	20	35
11	21	DIFFSENS	21	22	GROUND	22	36
12	23	RESERVED	23	24	RESERVED	24	37
13	25	TERMPWR	25	26	TERMPWR	26	38
14	27	RESERVED	27	28	RESERVED	28	39
15	29	+ATN	29	30	-ATN	30	40
16	31	GROUND	31	32	GROUND	32	41
17	33	+BSY	33	34	-BSY	34	42
18	35	+ACK	35	36	-ACK	36	43
19	37	+RST	37	38	-RST	38	44
20	39	+MSG	39	40	-MSG	40	45
21	41	+SEL	41	42	-SEL	42	46
22	43	+C/D	43	44	-C/D	44	47
23	45	+REQ	45	46	-REQ	46	48
24	47	+I/O	47	48	-I/O	48	49
25	49	GROUND	49	50	GROUND	50	50

- NOTES: 1) The conductor number refers to the conductor position when using 0.050" centerline flat ribbon cable with a low-density connector or when using 0.025" centerline flat ribbon cable with a high-density connector. Other cable types may be used to implement equivalent contact assignments.
- 3) Two sets of contact assignments are shown. Set 1 applies to the low density internal device connector only. Set 2 applies to all other connector styles.

TABLE 6-3 SINGLE ENDED: CONNECTOR CONTACTS FOR SCSI-3 P-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SCSI-3 Connector Contact and Signal Name	Single Ended P-Cable Conductor Position	68-pin SCSI-3 Connector Contact and Signal Name	
1 GROUND	1	2	-DB(12) 35
2 GROUND	3	4	-DB(13) 36
3 GROUND	5	6	-DB(14) 37
4 GROUND	7	8	-DB(15) 38
5 GROUND	9	10	-DB(P1) 39
6 GROUND	11	12	-DB(0) 40
7 GROUND	13	14	-DB(1) 41
8 GROUND	15	16	-DB(2) 42
9 GROUND	17	18	-DB(3) 43
10 GROUND	19	20	-DB(4) 44
11 GROUND	21	22	-DB(5) 45
12 GROUND	23	24	-DB(6) 46
13 GROUND	25	26	-DB(7) 47
14 GROUND	27	28	-DB(P) 48
15 GROUND	29	30	GROUND 49
16 GROUND	31	32	GROUND 50
17 TERMPWR	33	34	TERMPWR 51
18 TERMPWR	35	36	TERMPWR 52
19 RESERVED	37	38	RESERVED 53
20 GROUND	39	40	GROUND 54
21 GROUND	41	42	-ATN 55
22 GROUND	43	44	GROUND 56
23 GROUND	45	46	-BSY 57
24 GROUND	47	48	-ACK 58
25 GROUND	49	50	-RST 59
26 GROUND	51	52	-MSG 60
27 GROUND	53	54	-SEL 61
28 GROUND	55	56	-C/D 62
29 GROUND	57	58	-REQ 63
30 GROUND	59	60	-I/O 64
31 GROUND	61	62	-DB(8) 65
32 GROUND	63	64	-DB(9) 66
33 GROUND	65	66	-DB(10) 67
34 GROUND	67	68	-DB(11) 68

NOTE: 1) The conductor number refers to the conductor position when using 0.635mm (0.025) centerline flat-ribbon cable.

TABLE 6-4 DIFFERENTIAL: CONNECTOR CONTACTS FOR SCSI-3 P-CABLE

68-pin SCSI-3 Connector Contact and Signal Name	Differential P-Cable Conductor Position	68-pin SCSI-3 Connector Contact and Signal Name
1 +DB(12)	1	2 -DB(12) 35
2 +DB(13)	3	4 -DB(13) 36
3 +DB(14)	5	6 -DB(14) 37
4 +DB(15)	7	8 -DB(15) 38
5 +DB(P1)	9	10 -DB(P1) 39
6 GROUND	11	12 GROUND 40
7 +DB(0)	13	14 -DB(0) 41
8 +DB(1)	15	16 -DB(1) 42
9 +DB(2)	17	18 -DB(2) 43
10 +DB(3)	19	20 -DB(3) 44
11 +DB(4)	21	22 -DB(4) 45
12 +DB(5)	23	24 -DB(5) 46
13 +DB(6)	25	26 -DB(6) 47
14 +DB(7)	27	28 -DB(7) 48
15 +DB(P)	29	30 -DB(P) 49
16 DIFFSENS	31	32 GROUND 50
17 TERMPWR	33	34 TERMPWR 51
18 TERMPWR	35	36 TERMPWR 52
19 RESERVED	37	38 RESERVED 53
20 +ATN	39	40 -ATN 54
21 GROUND	41	42 GROUND 55
22 +BSY	43	44 -BSY 56
23 +ACK	45	46 -ACK 57
24 +RST	47	48 -RST 58
25 +MSG	49	50 -MSG 59
26 +SEL	51	52 -SEL 60
27 +C/D	53	54 -C/D 61
28 +REQ	55	56 -REQ 62
29 +I/O	57	58 -I/O 63
30 GROUND	59	60 GROUND 64
31 +DB(8)	61	62 -DB(8) 65
32 +DB(9)	63	64 -DB(9) 66
33 +DB(10)	65	66 -DB(10) 67
34 +DB(11)	67	68 -DB(11) 68

NOTE: 1) The conductor number refers to the conductor position when using 0.635mm (0.025) centerline flat-ribbon cable.

TABLE 6-5 SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8003 A-CABLE

50-pin SFF-8003 Connector Contact and Signal Name	Single Ended A-Cable Conductor Position	50-pin SFF-8003 Connector Contact and Signal Name
1 GROUND	1	2 -DB(0) 26
2 GROUND	3	4 -DB(1) 27
3 GROUND	5	6 -DB(2) 28
4 GROUND	7	8 -DB(3) 29
5 GROUND	9	10 -DB(4) 30
6 GROUND	11	12 -DB(5) 31
7 GROUND	13	14 -DB(6) 32
8 GROUND	15	16 -DB(7) 33
9 GROUND	17	18 -DB(P) 34
10 GROUND	19	20 GROUND 35
11 5V/3.3V GROUND	21	22 5V/3.3V (Motor) 36
12 12V/5V GROUND	23	24 12V/5V 37
13 TERMPWR	25	26 TERMPWR 38
14 12V/5V	27	28 12V/5V GROUND 39
15 5V/3.3V (Logic)	29	30 5V/3.3V (Return) 40
16 -ADDR #1/GROUND	31	32 -ATN 41
17 GROUND	33	34 SYNC 42
18 GROUND	35	36 -BSY 43
19 GROUND	37	38 -ACK 44
20 GROUND	39	40 -RST 45
21 -ADDR #2/GROUND	41	42 -MSG 46
22 GROUND	43	44 -SEL 47
23 -ADDR #3/GROUND	45	46 -C/D 48
24 GROUND	47	48 -REQ 49
25 VU/GROUND	49	50 -I/O 50

- NOTES: (1) The -ADDR #n/GROUND signals shall be externally grounded.  
(2) If more than one VU signal is required, the -ADDR #n/GROUND signals shall be used. See SFF-8003 for the recommended circuit to convert an -ADDR #n/GROUND signal to a VU Mode signal.  
(3) If the drive does not support on-board terminators, the TERMPWR signals shall not be connected to the drive.  
(4) Drives may be built for either 3.3V or 5V Logic.

TABLE 6-6 DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8003 A-CABLE

50-pin SFF-8003 Connector Contact and Signal Name	Differential A-Cable Conductor Position	50-pin SFF-8003 Connector Contact and Signal Name
1 +DB(0)	1	2 -DB(0)
2 +DB(1)	3	4 -DB(1)
3 +DB(2)	5	6 -DB(2)
4 +DB(3)	7	8 -DB(3)
5 +DB(4)	9	10 -DB(4)
6 +DB(5)	11	12 -DB(5)
7 +DB(6)	13	14 -DB(6)
8 +DB(7)	15	16 -DB(7)
9 +DB(P)	17	18 -DB(P)
10 DIFFSENS	19	20 GROUND
11 5V/3.3V GROUND	21	22 5V/3.3V (Motor)
12 12V/5V GROUND	23	24 12V/5V
13 TERMPWR	25	26 TERMPWR
14 12V/5V	27	28 12V/5V GROUND
15 5V/3.3V (Logic)	29	30 5V/3.3V (Return)
16 +ATN	31	32 -ATN
17 GROUND	33	34 SYNC
18 +BSY	35	36 -BSY
19 +ACK	37	38 -ACK
20 +RST	39	40 -RST
21 +MSG	41	42 -MSG
22 +SEL	43	44 -SEL
23 +C/D	45	46 -C/D
24 +REQ	47	48 -REQ
25 +I/O	49	50 -I/O

- NOTES: (1) The -ADDR #n/GROUND signals shall be externally grounded.  
(2) If more than one VU signal is required, the -ADDR #n/GROUND signals shall be used. See SFF-8003 for the recommended circuit to convert an -ADDR #n/GROUND signal to a VU Mode signal.  
(3) If the drive does not support on-board terminators, the TERMPWR signals shall not be connected to the drive.  
(4) Drives may be built for either 3.3V or 5V Logic.

TABLE 6-7 SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8003 P-CABLE

68-pin SFF-8003 Connector Contact and Signal Name	Single Ended P-Cable Conductor Position	68-pin SFF-8003 Connector Contact and Signal Name
1 GROUND	1	2 -DB(12) 35
2 GROUND	3	4 -DB(13) 36
3 GROUND	5	6 -DB(14) 37
4 GROUND	7	8 -DB(15) 38
5 GROUND	9	10 -DB(P1) 39
6 GROUND	11	12 -DB(0) 40
7 GROUND	13	14 -DB(1) 41
8 GROUND	15	16 -DB(2) 42
9 GROUND	17	18 -DB(3) 43
10 GROUND	19	20 -DB(4) 44
11 GROUND	21	22 -DB(5) 45
12 GROUND	23	24 -DB(6) 46
13 GROUND	25	26 -DB(7) 47
14 GROUND	27	28 -DB(P) 48
15 5V/3.3V GROUND	29	30 5V/3.3V (Motor) 49
16 12V/5V GROUND	31	32 12V/5V 50
17 TERMPWR	33	34 TERMPWR 51
18 TERMPWR	35	36 TERMPWR 52
19 12V/5V	37	38 12V/5V GROUND 53
20 5V/3.3V (Logic)	39	40 5V/3.3V (Return) 54
21 -ADDR #1/GROUND	41	42 -ATN 55
22 GROUND	43	44 SYNC 56
23 GROUND	45	46 -BSY 57
24 GROUND	47	48 -ACK 58
25 GROUND	49	50 -RST 59
26 -ADDR #2/GROUND	51	52 -MSG 60
27 GROUND	53	54 -SEL 61
28 -ADDR #3/GROUND	55	56 -C/D 62
29 GROUND	57	58 -REQ 63
30 -ADDR #4/GROUND	59	60 -I/O 64
31 GROUND	61	62 -DB(8) 65
32 GROUND	63	64 -DB(9) 66
33 GROUND	65	66 -DB(10) 67
34 GROUND	67	68 -DB(11) 68

- NOTES: (1) The -ADDR #n/GROUND signals shall be externally grounded.  
(2) If more than one VU signal is required, the -ADDR #n/GROUND signals shall be used. See SFF-8003 for the recommended circuit to convert an -ADDR #n/GROUND signal to a VU Mode signal.  
(3) If the drive does not support on-board terminators, the TERMPWR signals shall not be connected to the drive.  
(4) Drives may be built for either 3.3V or 5V Logic.  
(5) 8 bit drives which are connected to the SFF P-Cable shall leave the following signals open: -DB(P1) and -DB(8) through -DB(15). All other signals shall be connected as defined.

TABLE 6-8 DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8003 P-CABLE

68-pin SFF-8003 Connector Contact and Signal Name	Differential P-Cable Conductor Position	68-pin SFF-8003 Connector Contact and Signal Name
1 +DB(12)	1	2 -DB(12) 35
2 +DB(13)	3	4 -DB(13) 36
3 +DB(14)	5	6 -DB(14) 37
4 +DB(15)	7	8 -DB(15) 38
5 +DB(P1)	9	10 -DB(P1) 39
6 +DB(0)	11	12 -DB(0) 40
7 +DB(1)	13	14 -DB(1) 41
8 +DB(2)	15	16 -DB(2) 42
9 +DB(3)	17	18 -DB(3) 43
10 +DB(4)	19	20 -DB(4) 44
11 +DB(5)	21	22 -DB(5) 45
12 +DB(6)	23	24 -DB(6) 46
13 +DB(7)	25	26 -DB(7) 47
14 +DB(P)	27	28 -DB(P) 48
15 5V/3.3V GROUND	29	30 5V/3.3V (Motor) 49
16 12V/5V GROUND	31	32 12V/5V 50
17 TERMPWR	33	34 TERMPWR 51
18 TERMPWR	35	36 TERMPWR 52
19 12V/5V	37	38 12V/5V GROUND 53
20 5V/3.3V (Logic)	39	40 5V/3.3V (Return) 54
21 +ATN	41	42 -ATN 55
22 GROUND	43	44 DIFFSENS 56
23 +BSY	45	46 -BSY 57
24 +ACK	47	48 -ACK 58
25 +RST	49	50 -RST 59
26 +MSG	51	52 -MSG 60
27 +SEL	53	54 -SEL 61
28 +C/D	55	56 -C/D 62
29 +REQ	57	58 -REQ 63
30 +I/O	59	60 -I/O 64
31 +DB(8)	61	62 -DB(8) 65
32 +DB(9)	63	64 -DB(9) 66
33 +DB(10)	65	66 -DB(10) 67
34 +DB(11)	67	68 -DB(11) 68

- NOTES: (1) The -ADDR #n/GROUND signals shall be externally grounded.
- (2) If more than one VU signal is required, the -ADDR #n/GROUND signals shall be used. See SFF-8003 for the recommended circuit to convert an -ADDR #n/GROUND signal to a VU Mode signal.
- (3) If the drive does not support on-board terminators, the TERMPWR signals shall not be connected to the drive.
- (4) Drives may be built for either 3.3V or 5V Logic.
- (5) 8 bit drives which are connected to the SFF P-Cable shall leave the following signals open: -DB(P1) and -DB(8) through -DB(15). All other signals shall be connected as defined.

TABLE 6-9 SINGLE ENDED: SIGNAL ASSIGNMENTS FOR SFF-8015 SCA

80-pin SFF-8015 Connector Contact and Signal Name	Cable conductor numbers are not applicable.	80-pin SFF-8015 Connector Contact and Signal Name	
1 12V		12V GROUND	41
2 12V		12V GROUND	42
3 12V		12V GROUND	43
4 12V		12V GROUND	44
5 RESERVED/NC		RESERVED/NC	45
6 RESERVED/NC		RESERVED/NC	46
7 -DB(11)		GROUND	47
8 -DB(10)		GROUND	48
9 -DB(9)		GROUND	49
10 -DB(8)		GROUND	50
11 -I/O		GROUND	51
12 -REQ		GROUND	52
13 -C/D		GROUND	53
14 -SEL		GROUND	54
15 -MSG		GROUND	55
16 -RST		GROUND	56
17 -ACK		GROUND	57
18 -BSY		GROUND	58
19 -ATN		GROUND	59
20 -DB(P0)		GROUND	60
21 -DB(7)		GROUND	61
22 -DB(6)		GROUND	62
23 -DB(5)		GROUND	63
24 -DB(4)		GROUND	64
25 -DB(3)		GROUND	65
26 -DB(2)		GROUND	66
27 -DB(1)		GROUND	67
28 -DB(0)		GROUND	68
29 -DB(P1)		GROUND	69
30 -DB(15)		GROUND	70
31 -DB(14)		GROUND	71
32 -DB(13)		GROUND	72
33 -DB(12)		GROUND	73
34 5V		5V GROUND	74
35 5V		5V GROUND	75
36 5V		5V GROUND	76
37 SYNC		ACTIVE LED OUT	77
38 RMT_START		DLYD_START	78
39 SCSI ID(0)		SCSI ID (1)	79
40 SCSI ID(2)		SCSI ID (3)	80

TABLE 6-10 DIFFERENTIAL: SIGNAL ASSIGNMENTS FOR SFF-8015 SCA

80-pin SFF-8015 Connector Contact and Signal Name	Cable conductor numbers are not applicable.	80-pin SFF-8015 Connector Contact and Signal Name	
1 12V		12V GROUND	41
2 12V		12V GROUND	42
3 12V		12V GROUND	43
4 12V		12V GROUND	44
5 RESERVED/NC		RESERVED/NC	45
6 DIFFSENS		GROUND	46
7 -DB(11)		+DB(11)	47
8 -DB(10)		+DB(10)	48
9 -DB(9)		+DB(9)	49
10 -DB(8)		+DB(8)	50
11 -I/O		+I/O	51
12 -REQ		+REQ	52
13 -C/D		+C/D	53
14 -SEL		+SEL	54
15 -MSG		+MSG	55
16 -RST		+RST	56
17 -ACK		+ACK	57
18 -BSY		+BSY	58
19 -ATN		+ATN	59
20 -DB(P0)		+DB(P0)	60
21 -DB(7)		+DB(7)	61
22 -DB(6)		+DB(6)	62
23 -DB(5)		+DB(5)	63
24 -DB(4)		+DB(4)	64
25 -DB(3)		+DB(3)	65
26 -DB(2)		+DB(2)	66
27 -DB(1)		+DB(1)	67
28 -DB(0)		+DB(0)	68
29 -DB(P1)		+DB(P1)	69
30 -DB(15)		+DB(15)	70
31 -DB(14)		+DB(14)	71
32 -DB(13)		+DB(13)	72
33 -DB(12)		+DB(12)	73
34 5V		5V GROUND	74
35 5V		5V GROUND	75
36 5V		5V GROUND	76
37 SYNC		ACTIVE LED OUT	77
38 RMT_START		DLYD_START	78
39 SCSI ID(0)		SCSI ID (1)	79
40 SCSI ID(2)		SCSI ID (3)	80

TABLE 6-11 SINGLE ENDED: 68-PIN SCSI-3 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SCSI-3 Connector Contact and Signal Name		Single Ended A-Cable Conductor Position and Signal Name			68-pin SCSI-3 Connector Contact and Signal Name	
1 GROUND	*				* -DB(12)	35
2 GROUND	*				* -DB(13)	36
3 GROUND	*				* -DB(14)	37
4 GROUND	*				* -DB(15)	38
5 GROUND	*				* -DB(P1)	39
6 GROUND		1 GROUND	-DB(0)	2	-DB(0)	40
7 GROUND		3 GROUND	-DB(1)	4	-DB(1)	41
8 GROUND		5 GROUND	-DB(2)	6	-DB(2)	42
9 GROUND		7 GROUND	-DB(3)	8	-DB(3)	43
10 GROUND		9 GROUND	-DB(4)	10	-DB(4)	44
11 GROUND		11 GROUND	-DB(5)	12	-DB(5)	45
12 GROUND		13 GROUND	-DB(6)	14	-DB(6)	46
13 GROUND		15 GROUND	-DB(7)	16	-DB(7)	47
14 GROUND		17 GROUND	-DB(P)	18	-DB(P)	48
15 GROUND		19 GROUND	GROUND	20	GROUND	49
16 GROUND		21 GROUND	GROUND	22	GROUND	50
17 TERMPWR	X	23 RESERVED	RESERVED	24	X TERMPWR	51
18 TERMPWR	X	25 OPEN	TERMPWR	26	TERMPWR	52
19 RESERVED		27 RESERVED	RESERVED	28	RESERVED	53
20 GROUND		29 GROUND	GROUND	30	GROUND	54
21 GROUND		31 GROUND	-ATN	32	-ATN	55
22 GROUND		33 GROUND	GROUND	34	GROUND	56
23 GROUND		35 GROUND	-BSY	36	-BSY	57
24 GROUND		37 GROUND	-ACK	38	-ACK	58
25 GROUND		39 GROUND	-RST	40	-RST	59
26 GROUND		41 GROUND	-MSG	42	-MSG	60
27 GROUND		43 GROUND	-SEL	44	-SEL	61
28 GROUND		45 GROUND	-C/D	46	-C/D	62
29 GROUND		47 GROUND	-REQ	48	-REQ	63
30 GROUND		49 GROUND	-I/O	50	-I/O	64
31 GROUND	*				* -DB(8)	65
32 GROUND	*				* -DB(9)	66
33 GROUND	*				* -DB(10)	67
34 GROUND	*				* -DB(11)	68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = Normally no connection to the A-Cable conductor, but may be grounded or terminated for the benefit of the mating 68-signal bus. If grounded or terminated within a cable assembly, the cable assembly shall be so labeled.

TABLE 6-12 DIFFERENTIAL: 68-PIN SCSI-3 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SCSI-3 Connector Contact and Signal Name		Differential A-Cable Conductor Position and Signal Name			68-pin SCSI-3 Connector Contact and Signal Name	
1 +DB(12)	*				* -DB(12)	35
2 +DB(13)	*				* -DB(13)	36
3 +DB(14)	*				* -DB(14)	37
4 +DB(15)	*				* -DB(15)	38
5 +DB(P1)	*				* -DB(P1)	39
6 GROUND		1 GROUND	GROUND	2	GROUND	40
7 +DB(0)		3 +DB(0)	-DB(0)	4	-DB(0)	41
8 +DB(1)		5 +DB(L)	-DB(L)	6	-DB(1)	42
9 +DB(2)		7 +DB(2)	-DB(2)	8	-DB(2)	43
10 +DB(3)		9 +DB(3)	-DB(3)	10	-DB(3)	44
11 +DB(4)		11 +DB(4)	-DB(4)	12	-DB(4)	45
12 +DB(5)		13 +DB(5)	-DB(5)	14	-DB(5)	46
13 +DB(6)		15 +DB(6)	-DB(6)	16	-DB(6)	47
14 +DB(7)		17 +DB(7)	-DB(7)	18	-DB(7)	48
15 +DB(P)		19 +DB(P)	-DB(P)	20	-DB(P)	49
16 DIFFSENS		21 DIFFSENS	GROUND	22	GROUND	50
17 TERMPWR	X	23 RESERVED	RESERVED	24	X TERMPWR	51
18 TERMPWR		25 TERMPWR	TERMPWR	26	TERMPWR	52
19 RESERVED		27 RESERVED	RESERVED	28	RESERVED	53
20 +ATN		29 +ATN	-ATN	30	-ATN	54
21 GROUND		31 GROUND	GROUND	32	GROUND	55
22 +BSY		33 +BSY	-BSY	34	-BSY	56
23 +ACK		35 +ACK	-ACK	36	-ACK	57
24 +RST		37 +RST	-RST	38	-RST	58
25 +MSG		39 +MSG	-MSG	40	-MSG	59
26 +SEL		41 +SEL	-SEL	42	-SEL	60
27 +C/D		43 +C/D	-C/D	44	-C/D	61
28 +REQ		45 +REQ	-REQ	46	-REQ	62
29 +I/O		47 +I/O	-I/O	48	-I/O	63
30 GROUND		49 GROUND	GROUND	50	GROUND	64
31 +DB(8)	*				* -DB(8)	65
32 +DB(9)	*				* -DB(9)	66
33 +DB(10)	*				* -DB(10)	67
34 +DB(11)	*				* -DB(11)	68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = Normally no connection to the A-Cable conductor, but may be grounded or terminated for the benefit of the mating 68-signal bus. If grounded or terminated within a cable assembly, the cable assembly shall be so labeled.

TABLE 6-13 SINGLE ENDED: 50-PIN SFF-8003 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

50-pin SFF-8003	Single Ended A-Cable	50-pin SFF-8003
-----------------	----------------------	-----------------

Connector Contact and Signal Name	Conductor Position and Signal Name	Connector Contact and Signal Name
1 GROUND	1 GROUND -DB(0)	26 -DB(0)
2 GROUND	3 GROUND -DB(1)	27 -DB(1)
3 GROUND	5 GROUND -DB(2)	28 -DB(2)
4 GROUND	7 GROUND -DB(3)	29 -DB(3)
5 GROUND	9 GROUND -DB(4)	30 -DB(4)
6 GROUND	11 GROUND -DB(5)	31 -DB(5)
7 GROUND	13 GROUND -DB(6)	32 -DB(6)
8 GROUND	15 GROUND -DB(7)	33 -DB(7)
9 GROUND	17 GROUND -DB(P)	34 -DB(P)
10 GROUND	19 GROUND GROUND	35 GROUND
11 5V/3.3V GROUND X	21 GROUND GROUND	36 X 5V/3.3V (MOTOR)
12 12V/5V GROUND X	23 RESERVED RESERVED	37 X 12V/5V
13 TERMPWR X	25 OPEN TERMPWR	38 TERMPWR
14 12V/5V X	27 RESERVED RESERVED	39 X 12V/5V GROUND
15 5V/3.3V (LOGIC) X	29 GROUND GROUND	40 X 5V/3.3V (RETURN)
16 -ADDR #1/GROUND Y	31 GROUND -ATN	41 -ATN
17 GROUND	33 GROUND GROUND	42 X SYNC
18 GROUND	35 GROUND -BSY	43 -BSY
19 GROUND	37 GROUND -ACK	44 -ACK
20 GROUND	39 GROUND -RST	45 -RST
21 -ADDR #2/GROUND Y	41 GROUND -MSG	46 -MSG
22 GROUND	43 GROUND -SEL	47 -SEL
23 -ADDR #3/GROUND Y	45 GROUND -C/D	48 -C/D
24 GROUND	47 GROUND -REQ	49 -REQ
25 VU/GROUND Y	49 GROUND -I/O	50 -I/O

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

Y = If ADDR # is present then signal is Not Connected, otherwise it is connected as Ground.

No Reserved line functions are possible if used as a bussing connection

TABLE 6-14 DIFFERENTIAL: 50-PIN SFF-8003 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

50-pin SFF-8003 Connector Contact and Signal Name	Differential A-Cable Conductor Position and Signal Name	50-pin SFF-8003 Connector Contact and Signal Name
---	---	---

1	+DB(0)		1	+DB(0)	-DB(0)	2		-DB(0)	26
2	+DB(1)		3	+DB(1)	-DB(1)	4		-DB(1)	27
3	+DB(2)		5	+DB(2)	-DB(2)	6		-DB(2)	28
4	+DB(3)		7	+DB(3)	-DB(3)	8		-DB(3)	29
5	+DB(4)		9	+DB(4)	-DB(4)	10		-DB(4)	30
6	+DB(5)		11	+DB(5)	-DB(5)	12		-DB(5)	31
7	+DB(6)		13	+DB(6)	-DB(6)	14		-DB(6)	32
8	+DB(7)		15	+DB(7)	-DB(7)	16		-DB(7)	33
9	+DB(P)		17	+DB(P)	-DB(P)	18		-DB(P)	34
10	DIFFSENS		21	DIFFSENS	GROUND	20		GROUND	35
11	5V/3.3V GROUND	X	19	GROUND	GROUND	22	X	5V/3.3V (Motor)	36
12	12V/5V GROUND	X	23	RESERVED	RESERVED	24	X	12V/5V	37
13	TERMPWR		25	TERMPWR	TERMPWR	26		TERMPWR	38
14	12V/5V	X	27	RESERVED	RESERVED	28	X	12V/5V GROUND	39
15	5V/3.3V (Logic)	X	31	GROUND	GROUND	32	X	5V/3.3V (Return)	40
16	+ATN		29	+ATN	-ATN	30		-ATN	41
17	GROUND		33	GROUND	GROUND	34	X	SYNC	42
18	+BSY		35	+BSY	-BSY	36		-BSY	43
19	+ACK		37	+ACK	-ACK	38		-ACK	44
20	+RST		39	+RST	-RST	40		-RST	45
21	+MSG		41	+MSG	-MSG	42		-MSG	46
22	+SEL		43	+SEL	-SEL	44		-SEL	47
23	+C/D		45	+C/D	-C/D	46		-C/D	48
24	+REQ		47	+REQ	-REQ	48		-REQ	49
25	+I/O		49	+I/O	-I/O	50		-I/O	50

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.  
 No Reserved line functions are possible if used as a bussing connection

TABLE 6-15 SINGLE ENDED: 68-PIN SFF-8003 CONNECTION & SCSI-3 P-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SFF-8003 Connector Contact and Signal Name	Single Ended P-Cable Conductor Position and Signal Name	68-pin SFF-8003 Connector Contact and Signal Name
1 GROUND	1 GROUND -DB(12)	2 -DB(12) 35
2 GROUND	3 GROUND -DB(13)	4 -DB(13) 36
3 GROUND	5 GROUND -DB(14)	6 -DB(14) 37
4 GROUND	7 GROUND -DB(15)	8 -DB(15) 38
5 GROUND	9 GROUND -DB(P1)	10 -DB(P1) 39
6 GROUND	11 GROUND -DB(0)	12 -DB(0) 40
7 GROUND	13 GROUND -DB(1)	14 -DB(1) 41
8 GROUND	15 GROUND -DB(2)	16 -DB(2) 42
9 GROUND	17 GROUND -DB(3)	18 -DB(3) 43
10 GROUND	19 GROUND -DB(4)	20 -DB(4) 44
11 GROUND	21 GROUND -DB(5)	22 -DB(5) 45
12 GROUND	23 GROUND -DB(6)	24 -DB(6) 46
13 GROUND	25 GROUND -DB(7)	26 -DB(7) 47
14 GROUND	27 GROUND -DB(P)	28 -DB(P) 48
15 5V/3.3V GROUND X	29 GROUND GROUND	30 X 5V/3.3V (Motor) 49
16 12V/5V GROUND X	31 GROUND GROUND	32 X 12V/5V 50
17 TERMPWR	33 TERMPWR TERMPWR	34 TERMPWR 51
18 TERMPWR	35 TERMPWR TERMPWR	36 TERMPWR 52
19 12V/5V X	37 RESERVED RESERVED	38 X 12V/5V GROUND 53
20 5V/3V (Logic) X	39 GROUND GROUND	40 X 5V/3.3V (Return) 54
21 -ADDR #1/GROUND Y	41 GROUND -ATN	42 -ATN 55
22 GROUND	43 GROUND GROUND	44 X SYNC 56
23 GROUND	45 GROUND -BSY	46 -BSY 57
24 GROUND	47 GROUND -ACK	48 -ACK 58
25 GROUND	49 GROUND -RST	50 -RST 59
26 -ADDR #2/GROUND Y	51 GROUND -MSG	52 -MSG 60
27 GROUND	53 GROUND -SEL	54 -SEL 61
28 -ADDR #3/GROUND Y	55 GROUND -C/D	56 -C/D 62
29 GROUND	57 GROUND -REQ	58 -REQ 63
30 -ADDR #4/GROUND Y	59 GROUND -I/O	60 -I/O 64
31 GROUND	61 GROUND -DB(8)	62 -DB(8) 65
32 GROUND	63 GROUND -DB(9)	64 -DB(9) 66
33 GROUND	65 GROUND -DB(10)	66 -DB(10) 67
34 GROUND	67 GROUND -DB(11)	68 -DB(11) 68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

NOTE: Not recommended for bussing connections due to loss of Reserved line continuity.

TABLE 6-16 DIFFERENTIAL: 68-PIN SFF-8003 CONNECTION & SCSI-3 P-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SFF-8003 Connector Contact and Signal Name	Differential P-Cable Conductor Position and Signal Name	68-pin SFF-8003 Connector Contact and Signal Name
1 +DB(12)	1 +DB(12) -DB(12)	2 -DB(12) 35
2 +DB(13)	3 +DB(13) -DB(13)	4 -DB(13) 36
3 +DB(14)	5 +DB(14) -DB(14)	6 -DB(14) 37
4 +DB(15)	7 +DB(15) -DB(15)	8 -DB(15) 38
5 +DB(P1)	9 +DB(P1) -DB(P1)	10 -DB(P1) 39
6 +DB(0)	13 +DB(0) -DB(0)	14 -DB(0) 40
7 +DB(1)	15 +DB(1) -DB(1)	16 -DB(1) 41
8 +DB(2)	17 +DB(2) -DB(2)	18 -DB(2) 42
9 +DB(3)	19 +DB(3) -DB(3)	20 -DB(3) 43
10 +DB(4)	21 +DB(4) -DB(4)	22 -DB(4) 44
11 +DB(5)	23 +DB(5) -DB(5)	24 -DB(5) 45
12 +DB(6)	25 +DB(6) -DB(6)	26 -DB(6) 46
13 +DB(7)	27 +DB(7) -DB(7)	28 -DB(7) 47
14 +DB(P)	29 +DB(P) -DB(P)	30 -DB(P) 48
15 5V/3.3V GROUND X	11 GROUND GROUND	12 X 5V/3.3V (Motor) 49
16 12V/5V GROUND X	42 GROUND GROUND	32 X 12V/5V 50
17 TERMPWR	33 TERMPWR TERMPWR	34 TERMPWR 51
18 TERMPWR	35 TERMPWR TERMPWR	36 TERMPWR 52
19 12V/5V X	37 RESERVED RESERVED	38 X 12V/5V GROUND 53
20 5V/3V (Logic) X	59 GROUND GROUND	60 X 5V/3.3V (Return) 54
21 +ATN	39 +ATN -ATN	40 -ATN 55
22 GROUND	41 GROUND DIFFSENS	31 DIFFSENS 56
23 +BSY	43 +BSY -BSY	44 -BSY 57
24 +ACK	45 +ACK -ACK	46 -ACK 58
25 +RST	47 +RST -RST	48 -RST 59
26 +MSG	49 +MSG -MSG	50 -MSG 60
27 +SEL	51 +SEL -SEL	52 -SEL 61
28 +C/D	53 +C/D -C/D	54 -C/D 62
29 +REQ	55 +REQ -REQ	56 -REQ 63
30 +I/O	57 +I/O -I/O	58 -I/O 64
31 +DB(8)	61 +DB(8) -DB(8)	62 -DB(8) 65
32 +DB(9)	63 +DB(9) -DB(9)	64 -DB(9) 66
33 +DB(10)	65 +DB(10) -DB(10)	66 -DB(10) 67
34 +DB(11)	67 +DB(11) -DB(11)	68 -DB(11) 68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

NOTE: Not recommended for bussing connections due to loss of Reserved line continuity and no TERMPWR return path in cable (except for shell).

TABLE 6-17 SINGLE ENDED: 68-PIN SFF-8003 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SFF-8003 Connector Contact and Signal Name		Single Ended A-Cable Conductor Position and Signal Name			68-pin SFF-8003 Connector Contact and Signal Name	
1 GROUND	*				* -DB(12)	35
2 GROUND	*				* -DB(13)	36
3 GROUND	*				* -DB(14)	37
4 GROUND	*				* -DB(15)	38
5 GROUND					* -DB(P1)	39
6 GROUND		1 GROUND	-DB(0)	2	-DB(0)	40
7 GROUND		3 GROUND	-DB(1)	4	-DB(1)	41
8 GROUND		5 GROUND	-DB(2)	6	-DB(2)	42
9 GROUND		7 GROUND	-DB(3)	8	-DB(3)	43
10 GROUND		9 GROUND	-DB(4)	10	-DB(4)	44
11 GROUND		11 GROUND	-DB(5)	12	-DB(5)	45
12 GROUND		13 GROUND	-DB(6)	14	-DB(6)	46
13 GROUND		15 GROUND	-DB(7)	16	-DB(7)	47
14 GROUND		17 GROUND	-DB(P)	18	-DB(P)	48
15 5V/3.3V GROUND	X	19 GROUND	GROUND	20	X 5V/3.3V (Motor)	49
16 12V/5V GROUND	X	21 GROUND	GROUND	22	X 12V/5V	50
17 TERMPWR	X	23 RESERVED	RESERVED	24	X TERMPWR	51
18 TERMPWR	X	25 OPEN	TERMPWR	26	TERMPWR	52
19 12V/5V	X	27 RESERVED	RESERVED	28	X 12V/5V GROUND	53
20 5V/3V (Logic)	X	29 GROUND	GROUND	30	X 5V/3.3V (Return)	54
21 -ADDR #1/GROUND	Y	31 GROUND	-ATN	32	-ATN	55
22 GROUND		33 GROUND	GROUND	34	X SYNC	56
23 GROUND		35 GROUND	-BSY	36	-BSY	57
24 GROUND		37 GROUND	-ACK	38	-ACK	58
25 GROUND		39 GROUND	-RST	40	-RST	59
26 -ADDR #2/GROUND	Y	41 GROUND	-MSG	42	-MSG	60
27 GROUND		43 GROUND	-SEL	44	-SEL	61
28 -ADDR #3/GROUND	Y	45 GROUND	-C/D	46	-C/D	62
29 GROUND		47 GROUND	-REQ	48	-REQ	63
30 -ADDR #4/GROUND	Y	49 GROUND	-I/O	50	-I/O	64
31 GROUND	*				* -DB(8)	65
32 GROUND	*				* -DB(9)	66
33 GROUND	*				* -DB(10)	67
34 GROUND	*				* -DB(11)	68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

Y = If ADDR # is present then signal is Not Connected, otherwise it is connected as Ground.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: Not recommended for bussing connections due to loss of Reserved line continuity.

TABLE 6-18 DIFFERENTIAL: 68-PIN SFF-8003 CONNECTION & SCSI-2 A-CABLE  
(Applies to both bussing and stubbing connections)

68-pin SFF-8003 Connector Contact and Signal Name		Differential A-Cable Conductor Position and Signal Name			68-pin SFF-8003 Connector Contact and Signal Name	
1 +DB(12)	*				* -DB(12)	35
2 +DB(13)	*				* -DB(13)	36
3 +DB(14)	*				* -DB(14)	37
4 +DB(15)	*				* -DB(15)	38
5 +DB(P1)	*				* -DB(P1)	39
6 +DB(0)		3 +DB(0)	-DB(0)	4	-DB(0)	40
7 +DB(1)		5 +DB(1)	-DB(1)	6	-DB(1)	41
8 +DB(2)		7 +DB(2)	-DB(2)	8	-DB(2)	42
9 +DB(3)		9 +DB(3)	-DB(3)	10	-DB(3)	43
10 +DB(4)		11 +DB(4)	-DB(4)	12	-DB(4)	44
11 +DB(5)		13 +DB(5)	-DB(5)	14	-DB(5)	45
12 +DB(6)		15 +DB(6)	-DB(6)	16	-DB(6)	46
13 +DB(7)		17 +DB(7)	-DB(7)	18	-DB(7)	47
14 +DB(P)		19 +DB(P)	-DB(P)	20	-DB(P)	48
15 5V/3.3V GROUND	X	1 GROUND	GROUND	2	X 5V/3.3V (Motor)	49
16 12V/5V GROUND	X	49 GROUND	GROUND	50	X 12V/5V	50
17 TERMPWR	X	23 RESERVED	RESERVED	24	X TERMPWR	51
18 TERMPWR		25 TERMPWR	TERMPWR	26	TERMPWR	52
19 12V/5V	X	32 GROUND	GROUND	22	X 12V/5V GROUND	53
20 5V/3V (Logic)	X	27 RESERVED	RESERVED	28	X 5V/3.3V (Return)	54
21 +ATN		29 +ATN	-ATN	30	-ATN	55
22 GROUND		31 GROUND	DIFFSENS	21	DIFFSENS	56
23 +BSY		33 +BSY	-BSY	34	-BSY	57
24 +ACK		35 +ACK	-ACK	36	-ACK	58
25 +RST		37 +RST	-RST	38	-RST	59
26 +MSG		39 +MSG	-MSG	40	-MSG	60
27 +SEL		41 +SEL	-SEL	42	-SEL	61
28 +C/D		43 +C/D	-C/D	44	-C/D	62
29 +REQ		45 +REQ	-REQ	46	-REQ	63
30 +I/O		47 +I/O	-I/O	48	-I/O	64
31 +DB(8)	*				* -DB(8)	65
32 +DB(9)	*				* -DB(9)	66
33 +DB(10)	*				* -DB(10)	67
34 +DB(11)	*				* -DB(11)	68

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: Not recommended for bussing connections due to loss of Reserved line continuity.

TABLE 6-19 SINGLE ENDED: 80-PIN SFF-8015 CONNECTION TO SCSI-2 A-CABLE  
(Applies to stubbing connection)

80-pin SFF-8015 Connector Contact and Signal Name		Single Ended A-Cable Conductor Position and Signal Name			80-pin SFF-8015 Connector Contact and Signal Name	
1 12V	X				X 12V GROUND	41
2 12V	X				X 12V GROUND	42
3 12V	X				X 12V GROUND	43
4 12V	X				X 12V GROUND	44
5 RESERVED/NC	X	28 RESERVED	RESERVED	27	X RESERVED/NC	45
6 RESERVED/NC	X	24 RESERVED	RESERVED	23	X RESERVED/NC	46
7 -DB(11)	*		GROUND	20	GROUND	47
8 -DB(10)	*		GROUND	22	GROUND	48
9 -DB(9)	*		GROUND	28	GROUND	49
10 -DB(8)	*		GROUND	34	GROUND	50
11 -I/O		50 -I/O	GROUND	49	GROUND	51
12 -REQ		48 -REQ	GROUND	47	GROUND	52
13 -C/D		46 -C/D	GROUND	45	GROUND	53
14 -SEL		44 -SEL	GROUND	43	GROUND	54
15 -MSG		42 -MSG	GROUND	41	GROUND	55
16 -RST		40 -RST	GROUND	39	GROUND	56
17 -ACK		38 -ACK	GROUND	37	GROUND	57
18 -BSY		36 -BSY	GROUND	35	GROUND	58
19 -ATN		32 -ATN	GROUND	31	GROUND	59
20 -DB(P0)		18 -DB(P)	GROUND	17	GROUND	60
21 -DB(7)		16 -DB(7)	GROUND	15	GROUND	61
22 -DB(6)		14 -DB(6)	GROUND	13	GROUND	62
23 -DB(5)		12 -DB(5)	GROUND	11	GROUND	63
24 -DB(4)		10 -DB(4)	GROUND	9	GROUND	64
25 -DB(3)		8 -DB(3)	GROUND	7	GROUND	65
26 -DB(2)		6 -DB(2)	GROUND	5	GROUND	66
27 -DB(1)		4 -DB(1)	GROUND	3	GROUND	67
28 -DB(0)		2 -DB(0)	GROUND	1	GROUND	68
29 -DB(P1)	*		GROUND	19	GROUND	69
30 -DB(15)	*		GROUND	21	GROUND	70
31 -DB(14)	*		GROUND	29	GROUND	71
32 -DB(13)	*		GROUND	33	GROUND	72
33 -DB(12)	*		GROUND	30	GROUND	73
34 5V	X	26 TERMPWR	OPEN	25	X 5V GROUND	74
35 5V	X				X 5V GROUND	75
36 5V	X				X 5V GROUND	76
37 SYNC	X				X ACTIVE LED OUT	77
38 RMT_START	X				X DLYD_START	78
39 SCSI ID(0)	X				X SCSI ID (1)	79
40 SCSI ID(2)	X				X SCSI ID (3)	80

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: See also 5.5 Rack Mount Considerations

TABLE 6-20 SINGLE ENDED: 80-PIN SFF-8015 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

80-pin SFF-8015 Connector Contact and Signal Name		Single Ended P-Cable Conductor Position and Signal Name		80-pin SFF-8015 Connector Contact and Signal Name	
1 12V	X			X 12V GROUND	41
2 12V	X			X 12V GROUND	42
3 12V	X			X 12V GROUND	43
4 12V	X	32 GROUND	GROUND 31	X 12V GROUND	44
5 RESERVED/NC	X	38 RESERVED	RESERVED 37	X RESERVED/NC	45
6 RESERVED/NC	X	30 GROUND	GROUND 29	X RESERVED/NC	46
7 -DB(11)		68 -DB(11)	GROUND 67	GROUND	47
8 -DB(10)		66 -DB(10)	GROUND 65	GROUND	48
9 -DB(9)		64 -DB(9)	GROUND 63	GROUND	49
10 -DB(8)		62 -DB(8)	GROUND 61	GROUND	50
11 -I/O		60 -I/O	GROUND 59	GROUND	51
12 -REQ		58 -REQ	GROUND 57	GROUND	52
13 -C/D		56 -C/D	GROUND 55	GROUND	53
14 -SEL		54 -SEL	GROUND 53	GROUND	54
15 -MSG		52 -MSG	GROUND 51	GROUND	55
16 -RST		50 -RST	GROUND 49	GROUND	56
17 -ACK		48 -ACK	GROUND 47	GROUND	57
18 -BSY		46 -BSY	GROUND 45	GROUND	58
19 -ATN		42 -ATN	GROUND 41	GROUND	59
20 -DB(P0)		28 -DB(P)	GROUND 27	GROUND	60
21 -DB(7)		26 -DB(7)	GROUND 25	GROUND	61
22 -DB(6)		24 -DB(6)	GROUND 23	GROUND	62
23 -DB(5)		22 -DB(5)	GROUND 21	GROUND	63
24 -DB(4)		20 -DB(4)	GROUND 19	GROUND	64
25 -DB(3)		18 -DB(3)	GROUND 17	GROUND	65
26 -DB(2)		16 -DB(2)	GROUND 15	GROUND	66
27 -DB(1)		14 -DB(1)	GROUND 13	GROUND	67
28 -DB(0)		12 -DB(0)	GROUND 11	GROUND	68
29 -DB(P1)		10 -DB(P1)	GROUND 9	GROUND	69
30 -DB(15)		8 -DB(15)	GROUND 7	GROUND	70
31 -DB(14)		6 -DB(14)	GROUND 5	GROUND	71
32 -DB(13)		4 -DB(13)	GROUND 3	GROUND	72
33 -DB(12)		2 -DB(12)	GROUND 1	GROUND	73
34 5V	X	33 TERMPWR	GROUND 44	X 5V GROUND	74
35 5V	X	34 TERMPWR	GROUND 43	X 5V GROUND	75
36 5V	X	35 TERMPWR	GROUND 40	X 5V GROUND	76
37 SYNC	X	36 TERMPWR	GROUND 39	X ACTIVE LED OUT	77
38 RMT_START	X			X DLYD_START	78
39 SCSI ID(0)	X			X SCSI ID (1)	79
40 SCSI ID(2)	X			X SCSI ID (3)	80

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: See also 5.5 Rack Mount Considerations

TABLE 6-21 DIFFERENTIAL: 80-PIN SFF-8015 CONNECTION TO SCSI-2 A-CABLE  
(Applies to stubbing connection)

80-pin SFF-8015 Connector Contact and Signal Name		Differential A-Cable Conductor Position and Signal Name			80-pin SFF-8015 Connector Contact and Signal Name	
1 12V	X		GROUND	1	X 12V GROUND	41
2 12V	X		GROUND	2	X 12V GROUND	42
3 12V	X		GROUND	22	X 12V GROUND	43
4 12V	X		GROUND	31	X 12V GROUND	44
5 RESERVED/NC	X	28 RESERVED	RESERVED	27	X RESERVED/NC	45
6 DIFFSENS		21 DIFFSENS	RESERVED	23	X RESERVED/NC	46
7 -DB(11)	*				* +DB(11)	47
8 -DB(10)	*				* +DB(10)	48
9 -DB(9)	*				* +DB(9)	49
10 -DB(8)	*				* +DB(8)	50
11 -I/O		48 -I/O	+I/O	47	+I/O	51
12 -REQ		46 -REQ	+REQ	45	+REQ	52
13 -C/D		44 -C/D	+C/D	43	+C/D	53
14 -SEL		42 -SEL	+SEL	41	+SEL	54
15 -MSG		40 -MSG	+MSG	39	+MSG	55
16 -RST		38 -RST	+RST	37	+RST	56
17 -ACK		36 -ACK	+ACK	35	+ACK	57
18 -BSY		34 -BSY	+BSY	33	+BSY	58
19 -ATN		30 -ATN	+ATN	29	+ATN	59
20 -DB(PO)		20 -DB(P)	+DB(P)	19	+DB(PO)	60
21 -DB(7)		18 -DB(7)	+DB(7)	17	+DB(7)	61
22 -DB(6)		16 -DB(6)	+DB(6)	15	+DB(6)	62
23 -DB(5)		14 -DB(5)	+DB(5)	13	+DB(5)	63
24 -DB(4)		12 -DB(4)	+DB(4)	11	+DB(4)	64
25 -DB(3)		10 -DB(3)	+DB(3)	9	+DB(3)	65
26 -DB(2)		8 -DB(2)	+DB(2)	7	+DB(2)	66
27 -DB(1)		6 -DB(1)	+DB(1)	5	+DB(1)	67
28 -DB(0)		4 -DB(0)	+DB(0)	3	+DB(0)	68
29 -DB(P1)	*				* +DB(P1)	69
30 -DB(15)	*				* +DB(15)	70
31 -DB(14)	*				* +DB(14)	71
32 -DB(13)	*				* +DB(13)	72
33 -DB(12)	*				* +DB(12)	73
34 5V	X	26 TERMPWR	GROUND	32	X 5V GROUND	74
35 5V	X	25 TERMPWR	GROUND	49	X 5V GROUND	75
36 5V	X		GROUND	50	X 5V GROUND	76
37 SYNC	X		RESERVED	24	X ACTIVE LED OUT	77
38 RMT_START	X				X DLYD_START	78
39 SCSI ID(0)	X				X SCSI ID (1)	79
40 SCSI ID(2)	X				X SCSI ID (3)	80

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: See also 5.5 Rack Mount Considerations

TABLE 6-22 DIFFERENTIAL: 80-PIN SFF-8015 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

80-pin SFF-8015 Connector Contact and Signal Name		Differential P-Cable Conductor Position and Signal Name		80-pin SFF-8015 Connector Contact and Signal Name	
1 12V	X	GROUND	11	X 12V GROUND	41
2 12V	X	GROUND	12	X 12V GROUND	42
3 12V	X	GROUND	32	X 12V GROUND	43
4 12V	X	GROUND	41	X 12V GROUND	44
5 RESERVED/NC	X	38 RESERVED RESERVED	37	X RESERVED/NC	45
6 DIFFSENS		31 DIFFSENS		X RESERVED/NC	46
7 -DB(11)		68 -DB(11) +DB(11)	67	+DB(11)	47
8 -DB(10)		66 -DB(10) +DB(10)	65	+DB(10)	48
9 -DB(9)		64 -DB(9) +DB(9)	63	+DB(9)	49
10 -DB(8)		62 -DB(8) +DB(8)	61	+DB(8)	50
11 -I/O		58 -I/O +I/O	57	+I/O	51
12 -REQ		56 -REQ +REQ	55	+REQ	52
13 -C/D		54 -C/D +C/D	53	+C/D	53
14 -SEL		52 -SEL +SEL	51	+SEL	54
15 -MSG		50 -MSG +MSG	49	+MSG	55
16 -RST		48 -RST +RST	47	+RST	56
17 -ACK		46 -ACK +ACK	45	+ACK	57
18 -BSY		44 -BSY +BSY	43	+BSY	58
19 -ATN		40 -ATN +ATN	39	+ATN	59
20 -DB(PO)		30 -DB(P) +DB(P)	29	+DB(PO)	60
21 -DB(7)		28 -DB(7) +DB(7)	27	+DB(7)	61
22 -DB(6)		26 -DB(6) +DB(6)	25	+DB(6)	62
23 -DB(5)		24 -DB(5) +DB(5)	23	+DB(5)	63
24 -DB(4)		22 -DB(4) +DB(4)	21	+DB(4)	64
25 -DB(3)		20 -DB(3) +DB(3)	19	+DB(3)	65
26 -DB(2)		18 -DB(2) +DB(2)	17	+DB(2)	66
27 -DB(1)		16 -DB(1) +DB(1)	15	+DB(1)	67
28 -DB(0)		14 -DB(0) +DB(0)	13	+DB(0)	68
29 -DB(P1)		10 -DB(P1) +DB(P1)	9	+DB(P1)	69
30 -DB(15)		8 -DB(15) +DB(15)	7	+DB(15)	70
31 -DB(14)		6 -DB(14) +DB(14)	5	+DB(14)	71
32 -DB(13)		4 -DB(13) +DB(13)	3	+DB(13)	72
33 -DB(12)		2 -DB(13) +DB(12)	1	+DB(12)	73
34 5V	X	33 TERMPWR GROUND	42	X 5V GROUND	74
35 5V	X	34 TERMPWR GROUND	59	X 5V GROUND	75
36 5V	X	35 TERMPWR GROUND	60	X 5V GROUND	76
37 SYNC	X	36 TERMPWR		X ACTIVE LED OUT	77
38 RMT_START	X			X DLYD_START	78
39 SCSI ID(0)	X			X SCSI ID (1)	79
40 SCSI ID(2)	X			X SCSI ID (3)	80

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

\* = May be terminated/grounded in cable assembly (and should be so labeled). Signals should be negated on 8-bit devices with high value resistors to avoid false assertions.

NOTE: See also 5.5 Rack Mount Considerations

TABLE 6-23 SINGLE ENDED: 50-PIN SCSI-2 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

50-pin SCSI-2 Connector Contact and Signal Name		Single Ended P-Cable Conductor Position and Signal Name				50-pin SCSI-2 Connector Contact and Signal Name			
	X	1	GROUND	-DB(12)	2		X		
	X	3	GROUND	-DB(13)	4		X		
	X	5	GROUND	-DB(14)	6		X		
	X	7	GROUND	-DB(15)	8		X		
	X	9	GROUND	-DB(P1)	10		X		
1		11	GROUND	-DB(0)	12	-DB(0)	26		
2		13	GROUND	-DB(1)	14	-DB(1)	27		
3		15	GROUND	-DB(2)	16	-DB(2)	28		
4		17	GROUND	-DB(3)	18	-DB(3)	29		
5		19	GROUND	-DB(4)	20	-DB(4)	30		
6		21	GROUND	-DB(5)	22	-DB(5)	31		
7		23	GROUND	-DB(6)	24	-DB(6)	32		
8		25	GROUND	-DB(7)	26	-DB(7)	33		
9		27	GROUND	-DB(P)	28	-DB(P)	34		
10		29	GROUND	GROUND	30	GROUND	35		
11		31	GROUND	GROUND	32	GROUND	36		
12	RESERVED	X	33	TERMPWR	TERMPWR	34	X	RESERVED	37
13	OPEN	X	35	TERMPWR	TERMPWR	36		TERMPWR	38
14	RESERVED		37	RESERVED	RESERVED	38		RESERVED	39
15	GROUND		39	GROUND	GROUND	40		GROUND	40
16	GROUND		41	GROUND	-ATN	42		-ATN	41
17	GROUND		43	GROUND	GROUND	44		GROUND	42
18	GROUND		45	GROUND	-BSY	46		-BSY	43
19	GROUND		47	GROUND	-ACK	48		-ACK	44
20	GROUND		49	GROUND	-RST	50		-RST	45
21	GROUND		51	GROUND	-MSG	52		-MSG	46
22	GROUND		53	GROUND	-SEL	54		-SEL	47
23	GROUND		55	GROUND	-C/D	56		-C/D	48
24	GROUND		57	GROUND	-REQ	58		-REQ	49
25	GROUND		59	GROUND	-I/O	60		-I/O	50
	X	61	GROUND	-DB(8)	62		X		
	X	63	GROUND	-DB(9)	64		X		
	X	65	GROUND	-DB(10)	66		X		
	X	67	GROUND	-DB(11)	68		X		

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

TABLE 6-24 DIFFERENTIAL: 50-PIN SCSI-2 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

50-pin SCSI-2 Connector Contact and Signal Name		Differential P-Cable Conductor Position and Signal Name				50-pin SCSI-2 Connector Contact and Signal Name	
	X	1 +DB(12)	-DB(12)	2	X		
	X	3 +DB(13)	-DB(13)	4	X		
	X	5 +DB(14)	-DB(14)	6	X		
	X	7 +DB(15)	-DB(15)	8	X		
	X	9 +DB(P1)	-DB(P1)	10	X		
1 GROUND		11 GROUND	GROUND	12	GROUND		26
2 +DB(0)		13 +DB(0)	-DB(0)	14	-DB(0)		27
3 +DB(1)		15 +DB(1)	-DB(1)	16	-DB(1)		28
4 +DB(2)		17 +DB(2)	-DB(2)	18	-DB(2)		29
5 +DB(3)		19 +DB(3)	-DB(3)	20	-DB(3)		30
6 +DB(4)		21 +DB(4)	-DB(4)	22	-DB(4)		31
7 +DB(5)		23 +DB(5)	-DB(5)	24	-DB(5)		32
8 +DB(6)		25 +DB(6)	-DB(6)	26	-DB(6)		33
9 +DB(7)		27 +DB(7)	-DB(7)	28	-DB(7)		34
10 +DB(P)		29 +DB(P)	-DB(P)	30	-DB(P)		35
11 DIFFSENS		31 DIFFSENS	GROUND	32	GROUND		36
12 RESERVED	X	33 TERMPWR	TERMPWR	34	X RESERVED		37
13 TERMPWR		35 TERMPWR	TERMPWR	36	TERMPWR		38
14 RESERVED		37 RESERVED	RESERVED	38	RESERVED		39
15 +ATN		39 +ATN	-ATN	40	-ATN		40
16 GROUND		41 GROUND	GROUND	42	GROUND		41
17 +BSY		43 +BSY	-BSY	44	-BSY		42
18 +ACK		45 +ACK	-ACK	46	-ACK		43
19 +RST		47 +RST	-RST	48	-RST		44
20 +MSG		49 +MSG	-MSG	50	-MSG		45
21 +SEL		51 +SEL	-SEL	52	-SEL		46
22 +C/D		53 +C/D	-C/D	54	-C/D		47
23 +REQ		55 +REQ	-REQ	56	-REQ		48
24 +I/O		57 +I/O	-I/O	58	-I/O		49
25 GROUND		59 GROUND	GROUND	60	GROUND		50
	X	61 +DB(8)	-DB(8)	62	X		
	X	63 +DB(9)	-DB(9)	64	X		
	X	65 +DB(10)	-DB(10)	66	X		
	X	67 +DB(11)	-DB(11)	68	X		

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

TABLE 6-25 SINGLE ENDED: 50-PIN SFF-8003 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

50-pin SFF-8003 Connector Contact and Signal Name		Single Ended P-Cable Conductor Position and Signal Name				50-pin SFF-8003 Connector Contact and Signal Name		
	X	1	GROUND	-DB(12)	2		X	
	X	3	GROUND	-DB(13)	4		X	
	X	5	GROUND	-DB(14)	6		X	
	X	7	GROUND	-DB(15)	8		X	
	X	9	GROUND	-DB(P1)	10		X	
1		11	GROUND	-DB(0)	12	-DB(0)	26	
2		13	GROUND	-DB(1)	14	-DB(1)	27	
3		15	GROUND	-DB(2)	16	-DB(2)	28	
4		17	GROUND	-DB(3)	18	-DB(3)	29	
5		19	GROUND	-DB(4)	20	-DB(4)	30	
6		21	GROUND	-DB(5)	22	-DB(5)	31	
7		23	GROUND	-DB(6)	24	-DB(6)	32	
8		25	GROUND	-DB(7)	26	-DB(7)	33	
9		27	GROUND	-DB(P)	28	-DB(P)	34	
10		29	GROUND	GROUND	30	GROUND	35	
11	5V/3.3V GROUND	X	31	GROUND	GROUND	32	X 5V/3.3V (MOTOR)	36
12	12V/5V GROUND	X	33	TERMPWR	TERMPWR	34	X 12V/5V	37
13	TERMPWR		35	TERMPWR	TERMPWR	36	TERMPWR	38
14	12V/5V	X	37	RESERVED	RESERVED	38	X 12V/5V GROUND	39
15	5V/3.3V (LOGIC)	X	39	GROUND	GROUND	40	X 5V/3.3V (RETURN)	40
16	-ADDR #1/GROUND	Y	41	GROUND	-ATN	42	-ATN	41
17	GROUND		43	GROUND	GROUND	44	X SYNC	42
18	GROUND		45	GROUND	-BSY	46	-BSY	43
19	GROUND		47	GROUND	-ACK	48	-ACK	44
20	GROUND		49	GROUND	-RST	50	-RST	45
21	-ADDR #2/GROUND	Y	51	GROUND	-MSG	52	-MSG	46
22	GROUND		53	GROUND	-SEL	54	-SEL	47
23	-ADDR #3/GROUND	Y	55	GROUND	-C/D	56	-C/D	48
24	GROUND		57	GROUND	-REQ	58	-REQ	49
25	VU/GROUND	Y	59	GROUND	-I/O	60	-I/O	50
	X		61	GROUND	-DB(8)	62		X
	X		63	GROUND	-DB(9)	64		X
	X		65	GROUND	-DB(10)	66		X
	X		67	GROUND	-DB(11)	68		X

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

TABLE 6-26 DIFFERENTIAL: 50-PIN SFF-8003 CONNECTION TO SCSI-3 P-CABLE  
(Applies to stubbing connection)

50-pin SFF-8003 Connector Contact and Signal Name		Differential P-Cable Conductor Position and Signal Name					50-pin SFF-8003 Connector Contact and Signal Name	
	X	1	+DB(12)	-DB(12)	2	X		
	X	3	+DB(13)	-DB(13)	4	X		
	X	5	+DB(14)	-DB(14)	6	X		
	X	7	+DB(15)	-DB(15)	8	X		
	X	9	+DB(P1)	-DB(P1)	10	X		
12 12V/5V GROUND	X	11	GROUND	GROUND	12	X	12V/5V GROUND	39
1 +DB(0)		13	+DB(0)	-DB(0)	14		-DB(0)	26
2 +DB(1)		15	+DB(1)	-DB(1)	16		-DB(1)	27
3 +DB(2)		17	+DB(2)	-DB(2)	18		-DB(2)	28
4 +DB(3)		19	+DB(3)	-DB(3)	20		-DB(3)	29
5 +DB(4)		21	+DB(4)	-DB(4)	22		-DB(4)	30
6 +DB(5)		23	+DB(5)	-DB(5)	24		-DB(5)	31
7 +DB(6)		25	+DB(6)	-DB(6)	26		-DB(6)	32
8 +DB(7)		27	+DB(7)	-DB(7)	28		-DB(7)	33
9 +DB(P)		29	+DB(P)	-DB(P)	30		-DB(P)	34
10 DIFFSENS		31	DIFFSENS	GROUND	32		GROUND	35
11 5V/3.3V GROUND	X	33	TERMPWR	TERMPWR	34	X	5V/3.3V (Motor)	36
13 TERMPWR		35	TERMPWR	TERMPWR	36		TERMPWR	38
14 12V/5V	X	37	RESERVED	RESERVED	38	X	12V/5V	37
16 +ATN		39	+ATN	-ATN	40		-ATN	41
17 GROUND		41	GROUND	GROUND	42	X	SYNC	42
18 +BSY		43	+BSY	-BSY	44		-BSY	43
19 +ACK		45	+ACK	-ACK	46		-ACK	44
20 +RST		47	+RST	-RST	48		-RST	45
21 +MSG		49	+MSG	-MSG	50		-MSG	46
22 +SEL		51	+SEL	-SEL	52		-SEL	47
23 +C/D		53	+C/D	-C/D	54		-C/D	48
24 +REQ		55	+REQ	-REQ	56		-REQ	49
25 +I/O		57	+I/O	-I/O	58		-I/O	50
15 5V/3.3V (Logic)	X	59	GROUND	GROUND	60	X	5V/3.3V (Return)	40
	X	61	+DB(8)	-DB(8)	62	X		
	X	63	+DB(9)	-DB(9)	64	X		
	X	65	+DB(10)	-DB(10)	66	X		
	X	67	+DB(11)	-DB(11)	68	X		

X = Signal is Not Connected i.e. no connection between the SFF connector pin and the respective cable conductor.

Y = If ADDR # is present then signal is Not Connected, otherwise it is connected as Ground.

TABLE 6-27 SINGLE ENDED: SCSI-3 68 PIN CONNECTOR TO DUAL SCSI-2 A-CABLE  
(applies to stubbing and bussing connections)

BUS 1 50-pin SCSI-2 Connector Contact and Signal Name (Set 2)	68 PIN SCSI-3 Connector Contact and Signal Name			BUS 2 50 PIN SCSI-2 Connector Contact and Signal Name (Set 2)	
	BUS 1		BUS 2		
1 GROUND	1 GROUND	GROUND	1	GROUND	1
26 -DB0	2 -DB(0)	-DB(0)	35	-DB(0)	26
2 GROUND	36 GROUND	GROUND	36	GROUND	2
27 -DB(1)	3 -DB(1)	-DB(1)	37	-DB(1)	27
3 GROUND	4 GROUND	GROUND	4	GROUND	3
28 -DB(2)	5 -DB(2)	-DB(2)	38	-DB(2)	28
4 GROUND	39 GROUND	GROUND	39	GROUND	4
29 -DB(3)	6 -DB(3)	-DB(3)	40	-DB(3)	29
5 GROUND	7 GROUND	GROUND	7	GROUND	5
30 -DB(4)	8 -DB(4)	-DB(4)	41	-DB(4)	30
6 GROUND	42 GROUND	GROUND	42	GROUND	6
31 -DB(5)	9 -DB(5)	-DB(5)	43	-DB(5)	31
7 GROUND	10 GROUND	GROUND	10	GROUND	7
32 -DB(6)	11 -DB(6)	-DB(6)	44	-DB(6)	32
8 GROUND	45 GROUND	GROUND	45	GROUND	8
33 -DB(7)	12 -DB(7)	-DB(7)	46	-DB(7)	33
9 GROUND	16 GROUND	GROUND	16	GROUND	9
34 -DB(P)	13 -DB(P)	-DB(P)	47	-DB(P)	34
10 GROUND				X GROUND	10
35 GROUND/SWAP L	14 GND/SWP	GND/SWP	48	GROUND/SWAP L	35
11 GROUND				X GROUND	11
36 GROUND/SHLF OK H	15 GND/SHL	GND/SHL	49	GROUND/SHLF OK H	36
12 RESERVED				X RESERVED	12
37 RESERVED				X RESERVED	37
13 OPEN	17		51	X OPEN	13
38 TERMPWR	18 TERMPWR	TERMPWR	52	TERMPWR	38
14 RESERVED				X RESERVED	14
39 RESERVED	19 RESERVED	RESERVED	50	RESERVED	39
15 GROUND				X GROUND	15
40 GROUND/FLT CLK H	20 GND/FLTC	GND/FLTC	53	GROUND/FLT CLK H	40
16 GROUND	56 GROUND	GROUND	56	GROUND	16
41 -ATN	21 -ATN	-ATN	54	-ATN	41
17 GROUND				X GROUND	17
42 GROUND/FLT DAT A	22 GND/FLTD	GND/FLTD	55	GROUND/FLT DAT A	42
18 GROUND	24 GROUND	GROUND	24	GROUND	18
43 -BSY	23 -BSY	-BSY	57	-BSY	43
19 GROUND	59 GROUND	GROUND	59	GROUND	19
44 -ACK	25 -ACK	-ACK	58	-ACK	44
20 GROUND	27 GROUND	GROUND	27	GROUND	20
45 -RST	26 -RST	-RST	60	-RST	45
21 GROUND	62 GROUND	GROUND	62	GROUND	21
46 -MSG	28 -MSG	-MSG	61	-MSG	46
22 GROUND	30 GROUND	GROUND	30	GROUND	22
47 -SEL	29 -SEL	-SEL	63	-SEL	47
23 GROUND	65 GROUND	GROUND	65	GROUND	23
48 -C/D	31 -C/D	-C/D	64	-C/D	48
24 GROUND	33 GROUND	GROUND	33	GROUND	24
49 -REQ	32 -REQ	-REQ	66	-REQ	49
25 GROUND	68 GROUND	GROUND	68	GROUND	25
50 -I/O	34 -I/O	-I/O	67	-I/O	50

X = Signal is Not Connected i.e. no connection between the A cable conductor and any 68 pin connector pin.

Note: pins 17 and 51 on the 68 pin connector are not connected to prevent TERMPWR shorts if an ordinary P cable were accidentally mated to a dual A cable.

Note: SWAP, SHLF, FLT CLK, FLT DAT are optional non-SCSI signals used in RAID applications

Note: A 34 pair "P" cable CANNOT provide a dual "A" cable function.